

東芝照明器具配光データシート

名 称	LED照明器具	良	0.63			
形 名	LEDB83003	保守率	中	0.60		
			否	0.56		
光源	名称	LEDランプ	効 率	F 	16%	
	形名	LDM20SS・N/10/10		F 	65%	
	光束	1000 lm × 1		F 	81%	
前 面						
反射面						
			器具 光束	810 lm		
			最大取付間隔		天井取付 備考	
			A-A	1.3 H		
			B-B	1.5 H		

光度 (cd/1000lm)				反 射 率 (%)	天井	80			70			50		30	20	0								
$\theta \setminus \phi$	A-A	B-B	C-C		壁	70	50	30	70	50	30	50	30	30	10	0								
	A-A	B-B	C-C		床	30	10	30	10	30	10	30	10	30	10	0								
				室指数	照 明 率 (×0.01)																			
0°	145	145	145	0.60	44	40	31	30	24	23	41	38	30	29	23	23	28	27	22	21	20	20	16	14
10°	144	142	142	0.80	52	47	40	37	32	30	49	45	38	36	31	29	35	33	28	28	26	26	21	19
20°	139	145	139	1.00	58	52	45	42	37	35	54	49	43	40	36	34	39	37	33	32	30	30	25	22
30°	130	143	133	1.25	64	57	52	48	43	41	60	54	49	46	42	39	45	42	38	37	35	34	29	26
40°	118	139	124	1.50	68	60	56	51	48	44	64	57	54	49	46	43	48	45	42	40	39	37	33	29
50°	104	133	112	2.00	75	65	64	57	56	51	70	62	61	55	54	50	55	51	49	46	45	43	38	34
60°	88	126	100	2.50	79	68	69	61	62	55	74	65	66	59	59	54	59	54	53	50	48	46	42	38
70°	72	116	87	3.00	82	70	73	64	66	59	77	67	69	62	63	57	62	57	57	53	52	49	45	41
80°	57	106	75	4.00	86	73	79	68	72	64	81	70	74	66	69	61	66	61	62	57	56	53	49	45
90°	15	95	63	5.00	88	75	82	71	77	67	83	72	78	68	73	64	69	63	65	60	59	56	52	47
100°	0	82	52	10.00	94	79	90	76	87	74	89	76	85	74	82	71	76	69	73	67	66	62	59	54
110°	0	69	42																					
120°	0	55	34																					
130°	0	42	0																					
140°	0	0	0																					
150°	0	0	0																					
160°	0	0	0																					
170°	0	0	0																					
180°	0	0	0																					

