

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDD87025N (W) -LSX

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	750 lm

保守 率	良	0.67
	中	0.63
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備 考	
--------	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	447		
10°	449		
20°	421		
30°	363		
40°	303		
50°	206		
60°	116		
70°	39		
80°	6		
90°	1		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	10	0		
室指数	固有照明率 (×0.01)																								
0.60	69	63	55	53	48	46	67	62	55	52	47	46	53	51	46	45	46	45	41	39					
0.80	82	74	69	64	61	58	79	73	68	64	60	58	66	63	59	57	58	57	53	51					
1.00	88	79	76	71	68	64	86	78	75	70	67	64	72	68	66	63	64	62	59	57					
1.25	96	85	84	77	76	71	93	84	83	76	75	71	79	75	73	70	71	69	65	63					
1.50	100	89	90	81	82	76	97	87	88	81	81	75	84	79	78	74	76	73	70	68					
2.00	108	94	99	88	92	84	105	93	97	87	90	83	92	86	87	82	84	81	77	76					
2.50	112	97	104	92	98	88	109	95	101	91	95	87	96	89	92	86	88	85	82	80					
3.00	115	99	108	95	102	91	111	97	105	94	100	90	100	92	95	89	91	87	85	83					
4.00	119	101	113	98	108	95	115	100	110	97	106	94	104	95	100	93	96	91	89	87					
5.00	121	103	117	100	112	98	117	101	113	99	109	97	106	97	103	95	98	93	91	89					
10.00	126	105	123	104	121	103	121	104	119	103	117	102	111	101	110	100	104	98	96	94					

