

# 東芝照明器具配光データシート

名称	LED照明器具
形名	LEDG87038YL-LSX

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具光束	480 lm

保守率	良	0.67
	中	0.63
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備 考	
--------	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	352		
10°	349		
20°	335		
30°	301		
40°	255		
50°	209		
60°	153		
70°	93		
80°	38		
90°	1		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30						20						0																
	壁	70		50		30		70		50		30		50		30		30		10		0		30		10		0		10		0																
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10													
室指数	固有照明率 (×0.01)																																															
0.60	63	58	49	46	40	39	61	57	48	46	40	39	47	45	39	38	39	38	33	32																												
0.80	75	68	61	57	52	50	73	67	60	57	51	50	58	55	50	49	49	48	44	42																												
1.00	82	74	69	64	59	56	80	73	67	63	59	56	65	61	57	55	56	54	50	48																												
1.25	90	80	77	71	68	64	87	79	75	70	67	63	72	68	65	62	63	61	57	55																												
1.50	95	84	83	75	74	69	92	82	81	74	73	68	77	72	70	67	68	66	62	59																												
2.00	104	90	93	83	84	77	100	89	90	82	83	76	86	80	80	75	77	74	70	68																												
2.50	108	93	99	87	91	82	104	92	96	86	89	81	91	84	85	80	82	79	75	73																												
3.00	112	96	103	91	96	86	108	94	100	89	94	85	95	87	90	84	86	82	79	77																												
4.00	116	99	110	95	104	91	112	98	106	94	101	90	100	92	96	89	91	87	84	82																												
5.00	119	101	113	97	108	94	115	99	110	96	105	93	103	94	100	92	94	90	87	85																												
10.00	125	105	122	103	119	101	120	103	118	102	115	100	110	99	108	98	102	96	94	92																												

