

# 東芝照明器具配光データシート

名称	LED照明器具
形名	LEDS87035L-LSX-F2

--	--

効 率	F	12 %
	F	88 %
	F	100 %
	器具 光束	700 lm

保守 率	良	0.67
	中	0.63
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.23 H
B-B	1.23 H

備 考	
--------	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	342		
10°	345		
20°	337		
30°	295		
40°	213		
50°	136		
60°	92		
70°	74		
80°	57		
90°	45		
100°	35		
110°	26		
120°	19		
130°	14		
140°	4		
150°	0		
160°	1		
170°	1		
180°	1		

反 射 率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	10	0		
室指数	固有照明率 (×0.01)																								
0.60	63	58	50	47	41	40	61	56	48	46	41	40	46	44	39	38	38	37	33	31					
0.80	75	68	61	57	52	50	72	66	59	56	51	49	56	53	49	48	47	46	42	39					
1.00	81	73	68	63	59	56	78	70	66	61	57	55	62	58	55	53	52	51	46	43					
1.25	88	78	75	69	66	62	84	76	73	67	64	61	68	64	61	58	58	56	51	48					
1.50	92	81	80	73	71	66	88	79	77	71	69	65	72	68	66	62	62	60	55	52					
2.00	100	87	89	80	81	74	95	84	86	78	78	72	79	74	73	69	69	66	62	58					
2.50	104	90	94	83	87	78	99	87	91	81	84	76	84	77	78	73	73	70	66	62					
3.00	107	92	99	86	91	82	102	89	95	84	88	80	87	80	82	76	76	73	69	65					
4.00	112	95	104	90	98	86	106	92	100	88	94	84	91	84	87	80	81	77	73	69					
5.00	114	97	108	93	102	89	109	94	103	90	98	87	94	86	90	83	84	79	76	72					
10.00	120	101	116	98	113	96	114	98	111	96	108	94	101	91	98	89	90	85	82	78					

