

■ 東芝照明器具配光データシート

名 称	L E D照明器具
形 名	LEDP88095

光源	名称	LEDランプ
	形名	LDG11N-H/10 0W
	光束	1340 lm × 1

前 面	
反射面	

保守率	良	0.63
	中	0.60
	否	0.56

効 率	F 	1 2 %
	F 	7 7 %
	F 	8 9 %
	器 具 光 束	1 1 9 0 lm

--	--

最大取付間隔		備考	
A-A	1.4 H		
B-B	1.4 H		

光度 (cd/1000lm)			
$\theta \backslash \phi$	A-A	B-B	C-C
0°	191		
10°	189		
20°	184		
30°	174		
40°	159		
50°	141		
60°	122		
70°	103		
80°	80		
90°	45		
100°	32		
110°	31		
120°	29		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		照 明 率 (×0.01)																					
0.60		49	45	36	34	28	27	47	44	35	33	27	27	33	31	26	25	25	24	20	18		
0.80		59	54	46	43	37	35	56	52	44	41	36	35	41	39	34	33	32	31	27	24		
1.00		65	59	52	48	43	41	62	56	50	47	42	40	46	44	39	38	37	36	31	28		
1.25		72	64	59	54	50	47	68	62	57	52	48	46	52	49	45	43	42	41	36	33		
1.50		77	67	64	58	55	51	73	65	62	56	53	50	57	53	50	47	46	45	40	37		
2.00		84	73	73	65	64	59	80	70	70	63	62	57	64	59	58	54	54	52	47	43		
2.50		88	76	78	69	70	63	84	74	75	67	68	62	68	63	63	59	58	56	51	47		
3.00		92	79	83	72	75	67	87	76	79	70	72	65	72	66	67	62	62	59	54	51		
4.00		96	82	89	77	82	72	91	79	85	75	79	70	77	70	72	67	66	63	59	55		
5.00		99	84	93	79	87	75	94	81	88	77	83	74	80	73	76	70	70	66	62	58		
10.00		105	88	101	85	98	83	100	86	96	83	93	81	87	79	85	77	77	73	70	66		

