

東芝照明器具配光データシート

名 称		屋外スポットライト		保 守 率	良	0.69		
形 名		LEDG88902 (K)			中	0.67		
					否	0.63		
光 源	名 称	ミニクリLED		効 率	F 	2 %	最大取付間隔	
	形 名	LDA6L-H-E17 / S			F 	19 %		
	光 束	440 lm × 1			F 	21 %		
前 面		グローブ（フロスト）		器 具 光 束			A-A	0.79 H
反射面		塗装（黒）					B-B	0.79 H
							備 考	

光度 (cd/1000lm)				
$\theta \backslash \phi$	A-A	B-B	C-C	
0°	240			
10°	221			
20°	169			
30°	56			
40°	17			
50°	14			
60°	9			
70°	5			
80°	3			
90°	5			
100°	5			
110°	3			
120°	2			
130°	2			
140°	2			
150°	3			
160°	2			
170°	2			
180°	0			

反射率 (%)	天井	80						70						50				30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
室指数		照 明 率 (×0.01)																			
0.60		15	14	13	12	12	11	15	14	13	12	12	11	12	12	11	11	11	11	10	10
0.80		17	16	15	14	14	13	17	15	15	14	13	13	14	13	13	13	13	12	12	11
1.00		19	17	16	15	15	14	18	16	16	15	15	14	15	15	14	14	14	13	13	12
1.25		20	17	18	16	16	15	19	17	17	16	16	15	16	15	15	15	15	14	13	13
1.50		20	18	18	17	17	16	20	18	18	16	17	16	17	16	16	15	15	15	14	14
2.00		22	19	20	18	18	17	21	18	19	17	18	17	18	17	17	16	16	16	15	14
2.50		22	19	21	18	19	17	21	19	20	18	19	17	19	17	18	17	17	16	15	15
3.00		23	19	21	19	20	18	22	19	21	18	20	18	19	18	18	17	17	17	16	15
4.00		24	20	22	19	21	19	22	19	22	19	21	18	20	18	19	18	18	17	17	16
5.00		24	20	23	20	22	19	23	20	22	19	21	19	20	19	20	18	18	18	17	16
10.00		25	21	24	21	24	20	24	20	23	20	23	20	21	19	21	19	20	18	18	17

