

東芝照明器具配光データシート

名 称		屋外スポットライト		保守率	良	0.69		
形 名		LEDS88902 (K)			中	0.67		
					否	0.63		
光源	名 称	ミニクリLED		効 率	F 	2 %	最大取付間隔	
	形 名	LDA6L-H-E17 /S			F 	19 %		
	光 束	440 lm × 1			F 	21 %		
前 面		グローブ (フロスト)		器具光束	90 lm	A-A 0.79H		備考
反射面		塗装 (黒)			B-B 0.79H			

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50				30		20	0																			
0°	240	25°	109		壁	70		50		30		70		50		30		50		30		30		10	0																			
		30°	56		床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0																			
2°		35°	26		室指数																				照 明 率 (×0.01)																			
3°		40°	17		0.60		15	14	13	12	12	11	15	14	13	12	12	11	12	12	11	11	11	11	10	10																		
4°		45°	15		0.80		17	16	15	14	14	13	17	15	15	14	13	13	14	13	13	13	13	12	12	11																		
5°	234	50°	14		1.00		19	17	16	15	15	14	18	16	16	15	15	14	15	15	14	14	14	13	13	12																		
6°		55°	13		1.25		20	17	18	16	16	15	19	17	17	16	16	15	16	15	15	15	15	14	13	13																		
7°		60°	9		1.50		20	18	18	17	17	16	20	18	18	16	17	16	17	16	16	15	15	15	14	14																		
8°		65°	7		2.00		22	19	20	18	18	17	21	18	19	17	18	17	18	17	17	16	16	16	15	14																		
9°		70°	5		2.50		22	19	21	18	19	17	21	19	20	18	19	17	19	17	18	17	17	16	15	15																		
10°	221	75°	4		3.00		23	19	21	19	20	18	22	19	21	18	20	18	19	18	18	17	17	17	16	15																		
11°		80°	3		4.00		24	20	22	19	21	19	22	19	22	19	21	18	20	18	19	18	18	17	17	16																		
12°		85°	4		5.00		24	20	23	20	22	19	23	20	22	19	21	19	20	19	20	18	18	18	17	16																		
13°		90°	5		10.00		25	21	24	21	24	20	24	20	23	20	23	20	21	19	21	19	20	18	18	17																		
14°																																												
15°	208																																											
16°																																												
17°																																												
18°																																												
19°																																												
20°	169																																											

