

東芝照明器具配光データシート


名 称	LEDシーリングライト
形 名	LEDH84179L-LD

効 率	F 	8 %
	F 	9 2 %
	F 	1 0 0 %
	器具 光束	4 0 0 0 lm

保守率	良	0.63
	中	0.60
	否	0.56

前 面	カバー（乳白）
反射面	塗装（白）

最大取付間隔	
A-A	1.27 H
B-B	1.27 H

	
θ	
	
ϕ	

備考	
----	--

光度(cd/1000lm)			
$\theta \backslash \phi$	A-A	B-B	C-C
0°	292	292	292
10°	288	288	288
20°	275	275	275
30°	253	253	253
40°	222	222	222
50°	184	184	184
60°	141	141	141
70°	96	96	96
80°	55	55	55
90°	27	27	27
100°	15	15	15
110°	12	12	12
120°	11	11	11
130°	10	10	10
140°	10	10	10
150°	9	9	9
160°	7	7	7
170°	5	5	5
180°	5	5	5

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		固有照明率 (×0.01)																					
0.60		60	55	45	43	37	36	58	53	44	42	36	35	42	41	35	34	34	33	29	26		
0.80		72	65	57	54	48	46	69	63	56	52	47	45	53	50	45	44	43	42	38	35		
1.00		79	71	64	60	55	52	75	68	63	58	54	51	59	56	51	50	49	48	43	41		
1.25		86	77	73	67	63	59	83	74	70	65	61	58	66	62	59	56	56	54	49	47		
1.50		91	80	78	71	69	64	87	78	76	70	67	63	71	67	64	61	61	59	54	51		
2.00		100	87	88	79	79	72	95	84	85	77	77	71	79	74	73	69	69	66	62	59		
2.50		104	90	94	83	86	77	100	88	91	81	83	76	84	78	78	73	74	71	67	63		
3.00		108	93	99	87	91	81	103	90	95	85	88	80	88	81	83	77	78	74	70	67		
4.00		113	96	105	91	99	87	108	93	101	89	95	85	93	85	89	82	83	79	75	72		
5.00		115	98	109	94	103	90	110	95	105	92	100	88	97	88	93	85	86	82	79	75		
10.00		122	102	118	100	115	97	116	100	113	98	110	96	104	94	101	92	94	89	86	82		

