

東芝照明器具配光データシート

名 称		東芝LED器具		θ 
形 名		LEKT423521HN-LD9		
効 率	F 	5 %		備考
	F 	95 %		
	F 	100 %		
	器具光束	5100 lm		
前 面		カバー (乳白)		
反射面		塗装 (白)		
最大取付間隔				
A-A		1.27 H		
B-B		1.23 H		

光度 (cd/1000lm)				反射率 (%)	天井	80			70			50			30		20	0
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70	50	30	70	50	30	50	30	50	30	30	10	0
0°	304	304	304	室指数	床	30	10	30	10	30	10	30	10	30	10	30	10	0
10°	299	298	299		固有照明率 (×0.01)													
20°	286	281	283	0.60	60	55	46	43	37	36	58	54	45	43	36	35	43	41
30°	263	253	258	0.80	72	65	57	54	48	46	69	63	56	53	47	45	53	51
40°	233	218	226	1.00	79	71	65	60	55	52	76	69	63	59	54	51	60	57
50°	198	176	187	1.25	87	77	73	67	63	59	83	75	71	65	62	58	67	63
60°	159	129	145	1.50	92	81	79	71	69	64	88	79	76	70	67	63	72	67
70°	121	79	103	2.00	100	87	88	79	79	72	96	85	86	77	77	71	80	75
80°	86	30	65	2.50	105	90	94	83	86	77	100	88	91	82	84	76	85	79
90°	58	2	38	3.00	108	93	99	87	91	81	104	91	96	85	89	80	89	82
100°	40	1	20	4.00	113	96	105	91	99	87	108	94	102	90	96	85	95	86
110°	13	1	1	5.00	116	98	109	94	104	90	111	96	105	92	100	89	98	89
120°	0	1	1	10.00	122	102	119	100	115	98	117	100	114	98	111	96	105	95
130°	0	1	0															
140°	0	0	0															
150°	0	0	0															
160°	0	0	0															
170°	1	0	0															
180°	1	1	0															

