


東芝照明器具配光データシート

名 称		東芝LED器具		<div><div>θ</div><div></div></div> <div><div>ϕ</div><div></div></div>			
形 名		LEKT423691W-LS9					
効 率	F 	5 %		保守率	良	0.88	
	F 	95 %			中	0.86	
	F 	100 %			否	0.81	
	器具光束	6700 lm		最大取付間隔			
前 面	カバー（乳白）			A-A	1.27 H	備考	
反射面	塗装（白）			B-B	1.23 H		

光度 (cd/1000lm)				反射率 (%)	天井 壁 床	80						70						50				30		20	0	
$\theta \backslash \phi$	A-A	B-B	C-C			70		50		30		70		50		30		50		30		30		10	0	
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
				室指数	固有照明率 (×0.01)																					
0°				0.60	60	55	46	43	37	36	58	54	45	43	36	35	43	41	35	34	34	34	29	27		
10°				0.80	72	65	57	54	48	46	69	63	56	53	47	45	53	51	46	44	44	43	38	36		
20°				1.00	79	71	65	60	55	52	76	69	63	59	54	51	60	57	52	50	50	49	44	42		
30°				1.25	87	77	73	67	63	59	83	75	71	65	62	58	67	63	59	57	57	55	50	48		
40°				1.50	92	81	79	71	69	64	88	79	76	70	67	63	72	67	65	61	62	60	55	52		
50°				2.00	100	87	88	79	79	72	96	85	86	77	77	71	80	75	74	69	70	68	63	60		
60°				2.50	105	90	94	83	86	77	100	88	91	82	84	76	85	79	79	74	75	72	68	65		
70°				3.00	108	93	99	87	91	81	104	91	96	85	89	80	89	82	84	78	79	76	72	69		
80°				4.00	113	96	105	91	99	87	108	94	102	90	96	85	95	86	90	83	85	81	77	74		
90°				5.00	116	98	109	94	104	90	111	96	105	92	100	89	98	89	94	86	88	84	80	77		
100°				10.00	122	102	119	100	115	98	117	100	114	98	111	96	105	95	103	93	96	90	88	85		
110°																										
120°																										
130°																										
140°																										
150°																										
160°																										
170°																										
180°																										

