

東芝照明器具配光データシート

名 称		東芝LED器具		<div><div><div><div><div></div><div>θ</div></div><div><div></div><div>0°</div></div></div><div><div><div><div></div><div>φ</div></div><div><div></div><div>0°</div></div></div><div><div><div><div></div><div>0°</div></div><div><div></div><div>0°</div></div></div><div><div><div><div></div><div>0°</div></div><div><div></div><div>0°</div></div></div></div></div></div></div></div>		
形 名		LEKT407201N-LD9				
効 率	F $\frac{1}{2}$	6 %		保 守 率	良	0.88
	F $\frac{3}{4}$	94 %			中	0.86
	F $\bigcirc$	100 %			否	0.81
	器具 光束	2000 lm		最大取付間隔		
前 面		カバー（乳白）		A-A		1.27 H
反射面		塗装（白）		B-B		1.23 H
				備 考		

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50				30		20	0
θ \ φ	A-A	B-B	C-C		壁	70		50		30		70		50		30		50		30		30		10	0
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
				室指数	固 有 照 明 率 (×0.01)																				
0°				0.60	60	55	46	43	37	36	58	54	44	42	36	35	42	41	35	34	34	33	29	27	
10°				0.80	72	65	57	54	48	46	69	63	56	53	47	45	53	51	45	44	44	43	38	36	
20°				1.00	79	71	64	60	55	52	76	69	63	59	54	51	59	56	52	50	50	48	43	41	
30°				1.25	86	77	73	67	63	59	83	75	70	65	61	58	66	63	59	56	56	55	50	47	
40°				1.50	91	80	78	71	69	64	88	78	76	70	67	63	71	67	64	61	61	59	54	52	
50°				2.00	100	87	88	79	79	72	95	84	85	77	77	71	80	74	73	69	69	67	62	59	
60°				2.50	104	90	94	83	86	77	100	88	91	81	83	76	85	78	79	74	74	71	67	64	
70°				3.00	108	93	99	87	91	81	103	90	95	85	88	80	89	81	83	77	78	75	71	68	
80°				4.00	113	96	105	91	99	87	108	94	101	89	95	85	94	86	89	82	84	80	76	73	
90°				5.00	116	98	109	94	103	90	111	96	105	92	100	88	97	88	93	85	87	83	79	76	
100°				10.00	122	102	118	100	115	97	117	100	113	98	110	96	104	94	102	92	95	89	87	83	
110°																									
120°																									
130°																									
140°																									
150°																									
160°																									
170°																									
180°																									

