


東芝照明器具配光データシート

名 称		東芝LED器具		θ 	
形 名		LEKT407521L-LD9			ϕ 
効 率	F 	6 %			
	F 	94 %			
	F 	100 %			
	器具光束	4700 lm			
保 守 率		良	0.88		
		中	0.86		
		否	0.81		
最大取付間隔				備考	
前 面		カバー (乳白)			
反射面		塗装 (白)			
		A-A	1.27 H		
		B-B	1.23 H		

光度 (cd/1000lm)				反射率 (%)	天井 壁 床	80						70						50				30		20	0			
$\theta \backslash \phi$	A-A	B-B	C-C			70		50		30		70		50		30		50		30		30		10	0			
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0		
				室指数	固有照明率 (×0.01)																							
0°				0.60	60	55	46	43	37	36	58	54	44	42	36	35	42	41	35	34	34	33	29	27				
10°				0.80	72	65	57	54	48	46	69	63	56	53	47	45	53	51	45	44	44	43	38	36				
20°				1.00	79	71	64	60	55	52	76	69	63	59	54	51	59	56	52	50	50	48	43	41				
30°				1.25	86	77	73	67	63	59	83	75	70	65	61	58	66	63	59	56	56	55	50	47				
40°				1.50	91	80	78	71	69	64	88	78	76	70	67	63	71	67	64	61	61	59	54	52				
50°				2.00	100	87	88	79	79	72	95	84	85	77	77	71	80	74	73	69	69	67	62	59				
60°				2.50	104	90	94	83	86	77	100	88	91	81	83	76	85	78	79	74	74	71	67	64				
70°				3.00	108	93	99	87	91	81	103	90	95	85	88	80	89	81	83	77	78	75	71	68				
80°				4.00	113	96	105	91	99	87	108	94	101	89	95	85	94	86	89	82	84	80	76	73				
90°				5.00	116	98	109	94	103	90	111	96	105	92	100	88	97	88	93	85	87	83	79	76				
100°				10.00	122	102	118	100	115	97	117	100	113	98	110	96	104	94	102	92	95	89	87	83				
110°																												
120°																												
130°																												
140°																												
150°																												
160°																												
170°																												
180°																												

