


東芝照明器具配光データシート

名 称		東芝LED器具		<div><div>θ</div><div></div></div> <div><div>ϕ</div><div></div></div>		
形 名		LEKT412401L-LD9				
効 率	F 	6 %		保 守 率	良	0.88
	F 	94 %			中	0.86
	F 	100 %			否	0.81
	器具光束	3600 lm		最大取付間隔		
前 面	カバー（乳白）		A-A	1.27 H	備 考	
反射面	塗装（白）		B-B	1.23 H		

光度 (cd/1000lm)				反射率 (%)	天井	80						70						50						30		20	0																												
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70			50			30			70			50			30			50		30	10	0																											
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0																											
	室指数																												固有照明率 (×0.01)																										
0°	301	301	301	0.60	60	55	46	43	37	36	58	54	44	42	36	35	43	41	35	34	34	33	29	27																															
10°	296	295	296	0.80	72	65	57	54	48	46	69	63	56	53	47	45	53	51	45	44	44	43	38	36																															
20°	283	278	280	1.00	79	71	64	60	55	52	76	69	63	59	54	51	59	56	52	50	50	49	44	41																															
30°	260	251	256	1.25	86	77	73	67	63	59	83	75	71	65	61	58	67	63	59	56	57	55	50	47																															
40°	231	215	224	1.50	91	81	78	71	69	64	88	78	76	70	67	63	72	67	64	61	61	59	55	52																															
50°	196	174	185	2.00	100	87	88	79	79	72	96	85	85	77	77	71	80	74	73	69	70	67	62	60																															
60°	158	128	144	2.50	105	90	94	83	86	77	100	88	91	82	83	76	85	79	79	74	75	72	67	64																															
70°	120	78	102	3.00	108	93	99	87	91	81	104	91	95	85	88	80	89	82	83	78	79	75	71	68																															
80°	85	30	64	4.00	113	96	105	91	99	87	108	94	101	89	95	85	94	86	89	83	84	80	76	73																															
90°	56	2	35	5.00	116	98	109	94	103	90	111	96	105	92	100	89	97	89	93	86	87	83	80	77																															
100°	34	1	18	10.00	122	102	118	100	115	98	117	100	114	98	110	96	105	95	102	93	95	90	87	84																															
110°	20	1	10																																																				
120°	13	1	7																																																				
130°	8	1	0																																																				
140°	0	0	0																																																				
150°	0	0	0																																																				
160°	0	0	0																																																				
170°	1	1	0																																																				
180°	1	1	1																																																				

