


東芝照明器具配光データシート

名 称		東芝LED器具		θ		
形 名		LEKT412691PWW-LS9				ϕ
効 率	F 	6 %		保 守 率	良	
	F 	94 %			中	0.86
	F 	100 %			否	0.81
	器具光束	6500 lm			最大取付間隔	
前 面		カバー (乳白)		備 考		
反射面		塗装 (白)				
A-A		1.27 H				
B-B		1.23 H				

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50						30		20	0				
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70			50			30			70			50			30			50		30		30		10	0
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0	
					固有照明率 (×0.01)																										
0°	301	301	301	室指数	0.60	60	55	46	43	37	36	58	54	44	42	36	35	43	41	35	34	34	33	29	27						
10°	296	295	296		0.80	72	65	57	54	48	46	69	63	56	53	47	45	53	51	45	44	44	43	38	36						
20°	283	278	280		1.00	79	71	64	60	55	52	76	69	63	59	54	51	59	56	52	50	50	49	44	41						
30°	260	251	256		1.25	86	77	73	67	63	59	83	75	71	65	61	58	67	63	59	56	57	55	50	47						
40°	231	215	224		1.50	91	81	78	71	69	64	88	78	76	70	67	63	72	67	64	61	61	59	55	52						
50°	196	174	185		2.00	100	87	88	79	79	72	96	85	85	77	77	71	80	74	73	69	70	67	62	60						
60°	158	128	144		2.50	105	90	94	83	86	77	100	88	91	82	83	76	85	79	79	74	75	72	67	64						
70°	120	78	102		3.00	108	93	99	87	91	81	104	91	95	85	88	80	89	82	83	78	79	75	71	68						
80°	85	30	64		4.00	113	96	105	91	99	87	108	94	101	89	95	85	94	86	89	83	84	80	76	73						
90°	56	2	35		5.00	116	98	109	94	103	90	111	96	105	92	100	89	97	89	93	86	87	83	80	77						
100°	34	1	18	10.00	122	102	118	100	115	98	117	100	114	98	110	96	105	95	102	93	95	90	87	84							
110°	20	1	10																												
120°	13	1	7																												
130°	8	1	0																												
140°	0	0	0																												
150°	0	0	0																												
160°	0	0	0																												
170°	1	1	0																												
180°	1	1	1																												

