

東芝照明器具配光データシート

名 称		東芝LED器具		<div><div>θ</div><div></div></div>			
形 名		LEKT412691W-LS9					
効 率	F 	6 %		保 守 率	良	0.88	
	F 	94 %			中	0.86	
	F 	100 %			否	0.81	
	器具光束	6700 lm		最大取付間隔			
前 面		カバー（乳白）		備 考	A-A		1.27 H
反射面		塗装（白）			B-B		1.23 H

光度 (cd/1000lm)				反射率 (%)	天井	80						70						50				30		20	0		
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70		50		30		70		50		30		50		30		30		10	0		
	0°	301	301		301	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
		10°	296		295		296	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
20°				283	278	280	固有照明率 (×0.01)																				
30°				260	251	256	室指数																				
40°				231	215	224	0.60	60	55	46	43	37	36	58	54	44	42	36	35	43	41	35	34	34	33	29	27
50°				196	174	185	0.80	72	65	57	54	48	46	69	63	56	53	47	45	53	51	45	44	44	43	38	36
60°				158	128	144	1.00	79	71	64	60	55	52	76	69	63	59	54	51	59	56	52	50	50	49	44	41
70°				120	78	102	1.25	86	77	73	67	63	59	83	75	71	65	61	58	67	63	59	56	57	55	50	47
80°				85	30	64	1.50	91	81	78	71	69	64	88	78	76	70	67	63	72	67	64	61	61	59	55	52
90°				56	2	35	2.00	100	87	88	79	79	72	96	85	85	77	77	71	80	74	73	69	70	67	62	60
100°				34	1	18	2.50	105	90	94	83	86	77	100	88	91	82	83	76	85	79	79	74	75	72	67	64
110°				20	1	10	3.00	108	93	99	87	91	81	104	91	95	85	88	80	89	82	83	78	79	75	71	68
120°				13	1	7	4.00	113	96	105	91	99	87	108	94	101	89	95	85	94	86	89	83	84	80	76	73
130°				8	1	0	5.00	116	98	109	94	103	90	111	96	105	92	100	89	97	89	93	86	87	83	80	77
140°				0	0	0	10.00	122	102	118	100	115	98	117	100	114	98	110	96	105	95	102	93	95	90	87	84
150°				0	0	0																					
160°				0	0	0																					
170°				1	1	0																					
180°				1	1	1																					

