

東芝照明器具配光データシート

名 称		東芝LED器具		θ 
形 名		LEKT415401N-LS9		
効 率	F 	0 %		備考
	F 	100 %		
	F 	100 %		
	器具光束	3800 lm		
最大取付間隔				
前 面		カバー（乳白）		
反射面		塗装（白）		
		A-A	1.27 H	
		B-B	1.23 H	

光度 (cd/1000lm)				反射率 (%)	天井	80			70			50			30		20	0
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70	50	30	70	50	30	50	30	50	30	30	10	0
0°	344	344	344		床	30	10	30	10	30	10	30	10	30	10	30	10	0
10°	337	337	336		固有照明率 (×0.01)													
20°	319	318	318	室指数	0.60	62	57	48	46	39	38	60	56	47	45	39	38	37
30°	293	288	289		0.80	75	68	60	57	51	49	72	66	59	56	50	49	48
40°	257	249	252		1.00	82	73	68	63	58	55	79	72	66	62	58	55	53
50°	215	203	207		1.25	90	80	76	70	67	63	87	78	75	69	66	62	60
60°	164	152	158		1.50	95	83	82	75	73	68	92	82	80	74	72	67	65
70°	102	96	102		2.00	103	90	92	82	84	77	100	88	90	81	82	76	74
80°	27	37	39		2.50	108	93	98	87	91	82	104	91	96	86	88	81	78
90°	0	2	2		3.00	112	96	103	90	96	86	108	94	100	89	94	85	83
100°	0	1	1		4.00	116	99	109	95	103	91	112	97	106	93	101	90	88
110°	0	1	1		5.00	119	101	113	97	108	94	115	99	110	96	105	93	91
120°	0	1	1		10.00	125	104	122	103	119	101	120	103	117	101	115	100	98
130°	0	1	1															
140°	0	1	1															
150°	0	1	1															
160°	0	1	0															
170°	1	1	1															
180°	1	1	1															

