

東芝照明器具配光データシート

名 称		東芝LED器具		<div><div><div><div><div><div></div><div>θ</div></div><div><div></div><div>0°</div></div></div><div><div></div><div>φ</div></div><div><div><div><div><div></div><div>C</div></div><div><div>A</div><div>C</div></div><div><div>B</div><div>B</div></div><div><div>C</div><div>A</div><div>C</div></div></div></div></div></div></div></div>			
形 名		LEKT415321L-LS9					
効 率	F $\frac{1}{2}$	0 %		保 守 率	良	0.86	
	F $\frac{1}{4}$	100 %			中	0.81	
	F○	100 %			否	0.72	
	器具 光束	2750 lm		最大取付間隔			
前 面	カバー（乳白）		A-A	1.27 H		備 考	
反射面	塗装（白）		B-B	1.23 H			

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50				30		20	0
θ \ φ	A-A	B-B	C-C		壁	70		50		30		70		50		30		50		30		30		10	0
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
				室指数	固 有 照 明 率 (×0.01)																				
0°				0.60	62	57	48	46	39	38	60	56	47	45	39	38	46	44	38	37	38	37	32	31	
10°				0.80	75	68	60	57	51	49	72	66	59	56	50	49	57	54	49	48	48	47	43	41	
20°				1.00	82	73	68	63	58	55	79	72	66	62	58	55	64	60	56	54	55	53	49	47	
30°				1.25	90	80	76	70	67	63	87	78	75	69	66	62	71	67	64	61	62	60	56	53	
40°				1.50	95	83	82	75	73	68	92	82	80	74	72	67	77	72	69	66	67	65	61	58	
50°				2.00	103	90	92	82	84	77	100	88	90	81	82	76	85	79	79	74	76	73	69	67	
60°				2.50	108	93	98	87	91	82	104	91	96	86	88	81	90	84	85	79	81	78	74	72	
70°				3.00	112	96	103	90	96	86	108	94	100	89	94	85	94	87	89	83	85	82	78	76	
80°				4.00	116	99	109	95	103	91	112	97	106	93	101	90	100	91	95	88	91	86	83	81	
90°				5.00	119	101	113	97	108	94	115	99	110	96	105	93	103	94	99	91	94	89	87	84	
100°				10.00	125	104	122	103	119	101	120	103	117	101	115	100	110	99	108	98	101	96	94	92	

