

東芝照明器具配光データシート

名 称		東芝LED器具		θ 
形 名		LEKT415691HPW-LS9		
効 率	F 	0 %		
	F 	100 %		
	F 	100 %		
	器具光束	6300 lm		
保 守 率		良	0.86	
		中	0.81	
		否	0.72	
最大取付間隔				備 考
A-A		1.27 H		
B-B		1.23 H		
前 面		カバー (乳白)		
反射面		塗装 (白)		

光度 (cd/1000lm)				反射率 (%)	天井 壁 床	80						70						50				30		20	0
$\theta \backslash \phi$	A-A	B-B	C-C			70	50		30		70	50		30		50		30		30		10	0		
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0	
	室指数					固有照明率 (×0.01)																			
0°	344	344	344	0.60	62	57	48	46	39	38	60	56	47	45	39	38	46	44	38	37	38	37	32	31	
10°	337	337	336	0.80	75	68	60	57	51	49	72	66	59	56	50	49	57	54	49	48	48	47	43	41	
20°	319	318	318	1.00	82	73	68	63	58	55	79	72	66	62	58	55	64	60	56	54	55	53	49	47	
30°	293	288	289	1.25	90	80	76	70	67	63	87	78	75	69	66	62	71	67	64	61	62	60	56	53	
40°	257	249	252	1.50	95	83	82	75	73	68	92	82	80	74	72	67	77	72	69	66	67	65	61	58	
50°	215	203	207	2.00	103	90	92	82	84	77	100	88	90	81	82	76	85	79	79	74	76	73	69	67	
60°	164	152	158	2.50	108	93	98	87	91	82	104	91	96	86	88	81	90	84	85	79	81	78	74	72	
70°	102	96	102	3.00	112	96	103	90	96	86	108	94	100	89	94	85	94	87	89	83	85	82	78	76	
80°	27	37	39	4.00	116	99	109	95	103	91	112	97	106	93	101	90	100	91	95	88	91	86	83	81	
90°	0	2	2	5.00	119	101	113	97	108	94	115	99	110	96	105	93	103	94	99	91	94	89	87	84	
100°	0	1	1	10.00	125	104	122	103	119	101	120	103	117	101	115	100	110	99	108	98	101	96	94	92	
110°	0	1	1																						
120°	0	1	1																						
130°	0	1	1																						
140°	0	1	1																						
150°	0	1	1																						
160°	0	1	0																						
170°	1	1	1																						
180°	1	1	1																						

