

東芝照明器具配光データシート

名 称		東芝LED器具		θ 0° φ A C C A B B C C				
形 名		LEKT415521PW-LS9						
効 率	F $\frac{1}{2}$	0 %		保 守 率	良	0.86		
	F $\frac{1}{4}$	100 %			中	0.81		
	F○	100 %			否	0.72		
	器具光束	4700 lm		最大取付間隔				
前 面	カバー（乳白）			A-A	1.27 H		備 考	
反射面	塗装（白）			B-B	1.23 H			

光度 (cd/1000lm)				反 射 率 (%)	天井 壁 床	80						70						50						30				20	0
$\theta \backslash \phi$	A-A	B-B	C-C			70						50						30						10	0				
						70		50		30		70		50		30		50		30		30		10	0				
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数					固 有 照 明 率 (×0.01)																								
0°	344	344	344	0.60	62	57	48	46	39	38	60	56	47	45	39	38	46	44	38	37	38	37	32	31					
10°	337	337	336	0.80	75	68	60	57	51	49	72	66	59	56	50	49	57	54	49	48	48	47	43	41					
20°	319	318	318	1.00	82	73	68	63	58	55	79	72	66	62	58	55	64	60	56	54	55	53	49	47					
30°	293	288	289	1.25	90	80	76	70	67	63	87	78	75	69	66	62	71	67	64	61	62	60	56	53					
40°	257	249	252	1.50	95	83	82	75	73	68	92	82	80	74	72	67	77	72	69	66	67	65	61	58					
50°	215	203	207	2.00	103	90	92	82	84	77	100	88	90	81	82	76	85	79	79	74	76	73	69	67					
60°	164	152	158	2.50	108	93	98	87	91	82	104	91	96	86	88	81	90	84	85	79	81	78	74	72					
70°	102	96	102	3.00	112	96	103	90	96	86	108	94	100	89	94	85	94	87	89	83	85	82	78	76					
80°	27	37	39	4.00	116	99	109	95	103	91	112	97	106	93	101	90	100	91	95	88	91	86	83	81					
90°	0	2	2	5.00	119	101	113	97	108	94	115	99	110	96	105	93	103	94	99	91	94	89	87	84					
100°	0	1	1	10.00	125	104	122	103	119	101	120	103	117	101	115	100	110	99	108	98	101	96	94	92					
110°	0	1	1																										
120°	0	1	1																										
130°	0	1	1																										
140°	0	1	1																										
150°	0	1	1																										
160°	0	1	0																										
170°	1	1	1																										
180°	1	1	1																										

