

東芝照明器具配光データシート

名 称		東芝LED器具		θ 
形 名		LEKT415401PW-LS9		
効 率	F 	0 %		
	F 	100 %		
	F 	100 %		
	器具光束	3600 lm		
最大取付間隔		良	0.86	
		中	0.81	
		否	0.72	
前 面		カバー（乳白）		備考
反射面		塗装（白）		

光度 (cd/1000lm)				反射率 (%)	天井	80						70						50				30		20	0			
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70			50			30			70			50			30			50		30	10	0
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0
0°	344	344	344		固有照明率 (×0.01)																							
10°	337	337	336																									
20°	319	318	318																									
30°	293	288	289																									
40°	257	249	252																									
50°	215	203	207																									
60°	164	152	158																									
70°	102	96	102																									
80°	27	37	39																									
90°	0	2	2																									
100°	0	1	1																									
110°	0	1	1																									
120°	0	1	1																									
130°	0	1	1																									
140°	0	1	1																									
150°	0	1	1																									
160°	0	1	0																									
170°	1	1	1																									
180°	1	1	1																									

