

東芝照明器具配光データシート

名 称		東芝LED器具		θ 
形 名		LEKT415321PL-LS9		
効 率	F 	0 %		備考
	F 	100 %		
	F 	100 %		
	器具光束	2750 lm		
最大取付間隔				
前 面		カバー（乳白）		
反射面		塗装（白）		
		A-A	1.27 H	
		B-B	1.23 H	

光度 (cd/1000lm)				反 射 率 (%)	天井 壁 床	80						70						50				30		20	0				
$\theta \backslash \phi$	A-A	B-B	C-C			70		50		30		70		50		30		50		30		30		10	0				
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0				
0°	344	344	344			固有照明率 (×0.01)																							
10°	337	337	336																										
20°	319	318	318																										
30°	293	288	289																										
40°	257	249	252																										
50°	215	203	207																										
60°	164	152	158																										
70°	102	96	102																										
80°	27	37	39																										
90°	0	2	2																										
100°	0	1	1																										
110°	0	1	1																										
120°	0	1	1																										
130°	0	1	1																										
140°	0	1	1																										
150°	0	1	1																										
160°	0	1	0																										
170°	1	1	1																										
180°	1	1	1																										

