

東芝照明器具配光データシート

|        |                                                                                     |                  |        |                                                                                                 |
|--------|-------------------------------------------------------------------------------------|------------------|--------|-------------------------------------------------------------------------------------------------|
| 名 称    |                                                                                     | 東芝LED器具          |        | $\theta$<br> |
| 形 名    |                                                                                     | LEKT415691YN-LD9 |        |                                                                                                 |
| 効 率    | F  | 0 %              |        | 備 考                                                                                             |
|        | F  | 100 %            |        |                                                                                                 |
|        | F  | 100 %            |        |                                                                                                 |
|        | 器具光束                                                                                | 6500 lm          |        |                                                                                                 |
| 最大取付間隔 |                                                                                     |                  |        |                                                                                                 |
| 前 面    |                                                                                     | カバー（乳白）          |        |                                                                                                 |
| 反射面    |                                                                                     | 塗装（白）            |        |                                                                                                 |
|        |                                                                                     | A-A              | 1.27 H |                                                                                                 |
|        |                                                                                     | B-B              | 1.23 H |                                                                                                 |

| 光度 (cd/1000lm)          |     |     |     | 反射率 (%) | 天井            | 80  |     |     | 70  |     |     | 50  |     |     | 30  |     | 20  | 0  |
|-------------------------|-----|-----|-----|---------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
| $\theta \setminus \phi$ | A-A | B-B | C-C |         | 壁             | 70  | 50  | 30  | 70  | 50  | 30  | 50  | 30  | 50  | 30  | 30  | 10  | 0  |
| 0°                      | 344 | 344 | 344 |         | 床             | 30  | 10  | 30  | 10  | 30  | 10  | 30  | 10  | 30  | 10  | 30  | 10  | 0  |
| 10°                     | 337 | 337 | 336 |         | 固有照明率 (×0.01) |     |     |     |     |     |     |     |     |     |     |     |     |    |
| 20°                     | 319 | 318 | 318 | 室指数     | 0.60          | 62  | 57  | 48  | 46  | 39  | 38  | 60  | 56  | 47  | 45  | 39  | 38  | 37 |
| 30°                     | 293 | 288 | 289 |         | 0.80          | 75  | 68  | 60  | 57  | 51  | 49  | 72  | 66  | 59  | 56  | 50  | 49  | 48 |
| 40°                     | 257 | 249 | 252 |         | 1.00          | 82  | 73  | 68  | 63  | 58  | 55  | 79  | 72  | 66  | 62  | 58  | 55  | 53 |
| 50°                     | 215 | 203 | 207 |         | 1.25          | 90  | 80  | 76  | 70  | 67  | 63  | 87  | 78  | 75  | 69  | 66  | 62  | 60 |
| 60°                     | 164 | 152 | 158 |         | 1.50          | 95  | 83  | 82  | 75  | 73  | 68  | 92  | 82  | 80  | 74  | 72  | 67  | 65 |
| 70°                     | 102 | 96  | 102 |         | 2.00          | 103 | 90  | 92  | 82  | 84  | 77  | 100 | 88  | 90  | 81  | 82  | 76  | 74 |
| 80°                     | 27  | 37  | 39  |         | 2.50          | 108 | 93  | 98  | 87  | 91  | 82  | 104 | 91  | 96  | 86  | 88  | 81  | 78 |
| 90°                     | 0   | 2   | 2   |         | 3.00          | 112 | 96  | 103 | 90  | 96  | 86  | 108 | 94  | 100 | 89  | 94  | 85  | 83 |
| 100°                    | 0   | 1   | 1   |         | 4.00          | 116 | 99  | 109 | 95  | 103 | 91  | 112 | 97  | 106 | 93  | 101 | 90  | 88 |
| 110°                    | 0   | 1   | 1   |         | 5.00          | 119 | 101 | 113 | 97  | 108 | 94  | 115 | 99  | 110 | 96  | 105 | 93  | 91 |
| 120°                    | 0   | 1   | 1   |         | 10.00         | 125 | 104 | 122 | 103 | 119 | 101 | 120 | 103 | 117 | 101 | 115 | 100 | 98 |
| 130°                    | 0   | 1   | 1   |         |               |     |     |     |     |     |     |     |     |     |     |     |     |    |
| 140°                    | 0   | 1   | 1   |         |               |     |     |     |     |     |     |     |     |     |     |     |     |    |
| 150°                    | 0   | 1   | 1   |         |               |     |     |     |     |     |     |     |     |     |     |     |     |    |
| 160°                    | 0   | 1   | 0   |         |               |     |     |     |     |     |     |     |     |     |     |     |     |    |
| 170°                    | 1   | 1   | 1   |         |               |     |     |     |     |     |     |     |     |     |     |     |     |    |
| 180°                    | 1   | 1   | 1   |         |               |     |     |     |     |     |     |     |     |     |     |     |     |    |

