


東芝照明器具配光データシート

名 称		東芝LED器具		θ		
形 名		LEKT415251YW-LD9			ϕ	
効 率	F 	0 %		保守率		良 0.86 中 0.81 否 0.72
	F 	100 %				
	F 	100 %				
	器具光束	2250 lm				
前 面		カバー (乳白)		備 考		
反射面		塗装 (白)				
最大取付間隔						
		A-A	1.27 H			
		B-B	1.23 H			

光度 (cd/1000lm)				反射率 (%)	天井	80						70						50						30		20	0						
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70			50			30			70			50			30			50			30			30		10	0
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0			
					固有照明率 (×0.01)																												
0°	344	344	344	室指数	0.60	62	57	48	46	39	38	60	56	47	45	39	38	46	44	38	37	38	37	32	31								
10°	337	337	336		0.80	75	68	60	57	51	49	72	66	59	56	50	49	57	54	49	48	48	47	43	41								
20°	319	318	318		1.00	82	73	68	63	58	55	79	72	66	62	58	55	64	60	56	54	55	53	49	47								
30°	293	288	289		1.25	90	80	76	70	67	63	87	78	75	69	66	62	71	67	64	61	62	60	56	53								
40°	257	249	252		1.50	95	83	82	75	73	68	92	82	80	74	72	67	77	72	69	66	67	65	61	58								
50°	215	203	207		2.00	103	90	92	82	84	77	100	88	90	81	82	76	85	79	79	74	76	73	69	67								
60°	164	152	158		2.50	108	93	98	87	91	82	104	91	96	86	88	81	90	84	85	79	81	78	74	72								
70°	102	96	102		3.00	112	96	103	90	96	86	108	94	100	89	94	85	94	87	89	83	85	82	78	76								
80°	27	37	39		4.00	116	99	109	95	103	91	112	97	106	93	101	90	100	91	95	88	91	86	83	81								
90°	0	2	2		5.00	119	101	113	97	108	94	115	99	110	96	105	93	103	94	99	91	94	89	87	84								
100°	0	1	1		10.00	125	104	122	103	119	101	120	103	117	101	115	100	110	99	108	98	101	96	94	92								
110°	0	1	1																														
120°	0	1	1																														
130°	0	1	1																														
140°	0	1	1																														
150°	0	1	1																														
160°	0	1	0																														
170°	1	1	1																														
180°	1	1	1																														

