



■ 東芝照明器具配光データシート

名 称	東芝LED器具
形 名	LEKT425521VW-LS9

効 率	F 	0 %	保守率	良	0.86
	F 	100 %		中	0.81
	F 	100 %		否	0.72
	器具 光束	4550 lm	最大取付間隔		

前 面	カバー（乳白）	A-A	1.27 H
反射面	塗装（白）	B-B	1.23 H

備考	
----	--

光度(cd/1000lm)				反射率 (%)	天井		80						70						50						30		20	0		
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70		50		30		70		50		30		50		30		30		10	0					
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0			
				室指数	固有照明率(×0.01)																									
0°				329	329	329																								
10°				323	322	322																								
20°				307	303	305																								
30°				282	273	277																								
40°				250	235	242																								
50°				215	189	200																								
60°				175	139	160																								
70°				127	84	112																								
80°				76	32	62																								
90°				0	0	0																								
100°				0	0	0																								
110°				0	0	0																								
120°				0	0	0																								
130°				0	0	0																								
140°				0	0	0																								
150°				0	0	0																								
160°				0	0	0																								
170°				1	1	0																								
180°				1	1	1																								

