

東芝照明器具配光データシート

名 称		東芝LED器具		θ 
形 名		LEKT425251N-LS9		
効 率	F 	0 %		
	F 	100 %		
	F 	100 %		
	器具光束	2400 lm		
最大取付間隔				備考
前 面		カバー（乳白）		
反射面		塗装（白）		
		A-A	1.27 H	
		B-B	1.23 H	

光度 (cd/1000lm)				反射率 (%)	天井	80			70			50			30		20	0
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70	50	30	70	50	30	50	30	50	30	30	10	0
0°	329	329	329		床	30	10	30	10	30	10	30	10	30	10	30	10	0
10°	323	322	322		固有照明率 (×0.01)													
20°	307	303	305	室指数	0.60	61	56	47	44	38	37	60	55	46	44	38	37	29
30°	282	273	277		0.80	73	67	59	55	49	47	71	65	58	54	49	47	39
40°	250	235	242		1.00	81	72	66	61	57	54	78	71	65	61	56	53	45
50°	215	189	200		1.25	88	78	75	68	65	61	85	77	73	67	64	60	51
60°	175	139	160		1.50	93	82	81	73	71	66	90	81	79	72	70	65	56
70°	127	84	112		2.00	102	89	91	81	82	75	98	87	88	80	80	74	65
80°	76	32	62		2.50	107	92	97	86	89	80	103	91	94	84	87	79	70
90°	0	0	0		3.00	111	95	102	89	94	84	107	93	99	88	92	83	74
100°	0	0	0		4.00	115	98	108	94	102	89	111	97	105	92	99	89	80
110°	0	0	0		5.00	118	100	112	96	107	93	114	99	109	95	104	92	83
120°	0	0	0		10.00	125	104	121	102	118	100	120	103	117	101	114	99	91
130°	0	0	0															
140°	0	0	0															
150°	0	0	0															
160°	0	0	0															
170°	1	1	0															
180°	1	1	1															

