


東芝照明器具配光データシート

名 称	東芝LED器具			θ 		
形 名	LEKT425401N-LD9					
効 率	F 	0 %	保 守 率	良	0.86	
	F 	100 %		中	0.81	
	F 	100 %		否	0.72	
	器具光束	3800 lm			最大取付間隔	
前 面	カバー (乳白)			A-A	1.27 H	備 考
反射面	塗装 (白)			B-B	1.23 H	

光度 (cd/1000lm)				反 射 率 (%)	天井 壁 床	80						70						50				30		20	0
$\theta \backslash \phi$	A-A	B-B	C-C			70		50		30		70		50		30		50		30		30		10	0
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
0°		329	329	329	固有照明率 (×0.01)																				
10°		323	322	322																					
20°		307	303	305																					
30°		282	273	277																					
40°		250	235	242																					
50°		215	189	200																					
60°		175	139	160																					
70°		127	84	112																					
80°		76	32	62																					
90°		0	0	0																					
100°		0	0	0																					
110°		0	0	0																					
120°		0	0	0																					
130°		0	0	0																					
140°		0	0	0																					
150°		0	0	0																					
160°		0	0	0																					
170°		1	1	0																					
180°		1	1	1																					

