


東芝照明器具配光データシート

|        |                                                                                     |                 |        |                                                                                                 |
|--------|-------------------------------------------------------------------------------------|-----------------|--------|-------------------------------------------------------------------------------------------------|
| 名 称    |                                                                                     | 東芝LED器具         |        | $\theta$<br> |
| 形 名    |                                                                                     | LEKT425401W-LD9 |        |                                                                                                 |
| 効 率    | F  | 0 %             |        | $\phi$<br>   |
|        | F  | 100 %           |        |                                                                                                 |
|        | F  | 100 %           |        |                                                                                                 |
|        | 器具光束                                                                                | 3600 lm         |        |                                                                                                 |
| 最大取付間隔 |                                                                                     |                 |        | 備考                                                                                              |
| 前 面    |                                                                                     | カバー（乳白）         |        |                                                                                                 |
| 反射面    |                                                                                     | 塗装（白）           |        |                                                                                                 |
|        |                                                                                     | A-A             | 1.27 H |                                                                                                 |
|        |                                                                                     | B-B             | 1.23 H |                                                                                                 |

| 光度 (cd/1000lm)          |     |     |     | 反射率 (%) | 天井                | 80  |     |     | 70  |     |     | 50  |     |     | 30  |     | 20 | 0   |
|-------------------------|-----|-----|-----|---------|-------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|
| $\theta \setminus \phi$ | A-A | B-B | C-C |         | 壁                 | 70  | 50  | 30  | 70  | 50  | 30  | 50  | 30  | 30  | 10  | 0   |    |     |
| 0°                      | 329 | 329 | 329 |         | 床                 | 30  | 10  | 30  | 10  | 30  | 10  | 30  | 10  | 30  | 10  | 30  | 10 | 0   |
| 10°                     | 323 | 322 | 322 |         | 室指数 固有照明率 (×0.01) |     |     |     |     |     |     |     |     |     |     |     |    |     |
| 20°                     | 307 | 303 | 305 |         | 0.60              | 61  | 56  | 47  | 44  | 38  | 37  | 60  | 55  | 46  | 44  | 38  | 37 | 45  |
| 30°                     | 282 | 273 | 277 |         | 0.80              | 73  | 67  | 59  | 55  | 49  | 47  | 71  | 65  | 58  | 54  | 49  | 47 | 56  |
| 40°                     | 250 | 235 | 242 |         | 1.00              | 81  | 72  | 66  | 61  | 57  | 54  | 78  | 71  | 65  | 61  | 56  | 53 | 62  |
| 50°                     | 215 | 189 | 200 |         | 1.25              | 88  | 78  | 75  | 68  | 65  | 61  | 85  | 77  | 73  | 67  | 64  | 60 | 70  |
| 60°                     | 175 | 139 | 160 |         | 1.50              | 93  | 82  | 81  | 73  | 71  | 66  | 90  | 81  | 79  | 72  | 70  | 65 | 75  |
| 70°                     | 127 | 84  | 112 |         | 2.00              | 102 | 89  | 91  | 81  | 82  | 75  | 98  | 87  | 88  | 80  | 80  | 74 | 84  |
| 80°                     | 76  | 32  | 62  |         | 2.50              | 107 | 92  | 97  | 86  | 89  | 80  | 103 | 91  | 94  | 84  | 87  | 79 | 89  |
| 90°                     | 0   | 0   | 0   |         | 3.00              | 111 | 95  | 102 | 89  | 94  | 84  | 107 | 93  | 99  | 88  | 92  | 83 | 93  |
| 100°                    | 0   | 0   | 0   |         | 4.00              | 115 | 98  | 108 | 94  | 102 | 89  | 111 | 97  | 105 | 92  | 99  | 89 | 99  |
| 110°                    | 0   | 0   | 0   |         | 5.00              | 118 | 100 | 112 | 96  | 107 | 93  | 114 | 99  | 109 | 95  | 104 | 92 | 102 |
| 120°                    | 0   | 0   | 0   |         | 10.00             | 125 | 104 | 121 | 102 | 118 | 100 | 120 | 103 | 117 | 101 | 114 | 99 | 109 |
| 130°                    | 0   | 0   | 0   |         |                   |     |     |     |     |     |     |     |     |     |     |     |    |     |
| 140°                    | 0   | 0   | 0   |         |                   |     |     |     |     |     |     |     |     |     |     |     |    |     |
| 150°                    | 0   | 0   | 0   |         |                   |     |     |     |     |     |     |     |     |     |     |     |    |     |
| 160°                    | 0   | 0   | 0   |         |                   |     |     |     |     |     |     |     |     |     |     |     |    |     |
| 170°                    | 1   | 1   | 0   |         |                   |     |     |     |     |     |     |     |     |     |     |     |    |     |
| 180°                    | 1   | 1   | 1   |         |                   |     |     |     |     |     |     |     |     |     |     |     |    |     |

