

東芝照明器具配光データシート

名 称		東芝LED器具		<div><div><div><div><div></div><div>θ</div></div><div><div></div><div>0°</div></div></div><div><div><div><div></div><div>φ</div></div><div><div></div><div>A</div><div>C</div><div>C</div><div>A</div></div></div><div><div></div><div>B</div><div>B</div></div></div></div></div>		
形 名		LEKT425401WW-LD9				
効 率	F	0 %		保 守 率	良	0.86
	F	100 %			中	0.81
	F	100 %			否	0.72
	器具 光束	3500 lm		最大取付間隔		
前 面		カバー（乳白）		A-A	1.27 H	
反射面		塗装（白）		B-B	1.23 H	
				備 考		

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50				30		20	0		
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70		50		30		70		50		30		50		30		30		10	0		
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
						固 有 照 明 率 (×0.01)																					
0°	329	329	329	室指数	0.60	61	56	47	44	38	37	60	55	46	44	38	37	45	43	37	36	36	36	31	29		
10°	323	322	322		0.80	73	67	59	55	49	47	71	65	58	54	49	47	56	53	48	46	47	46	41	39		
20°	307	303	305		1.00	81	72	66	61	57	54	78	71	65	61	56	53	62	59	54	52	53	52	47	45		
30°	282	273	277		1.25	88	78	75	68	65	61	85	77	73	67	64	60	70	66	62	59	60	58	54	51		
40°	250	235	242		1.50	93	82	81	73	71	66	90	81	79	72	70	65	75	70	68	64	65	63	59	56		
50°	215	189	200		2.00	102	89	91	81	82	75	98	87	88	80	80	74	84	78	77	73	74	71	67	65		
60°	175	139	160		2.50	107	92	97	86	89	80	103	91	94	84	87	79	89	82	83	78	79	76	72	70		
70°	127	84	112		3.00	111	95	102	89	94	84	107	93	99	88	92	83	93	86	88	82	84	80	76	74		
80°	76	32	62		4.00	115	98	108	94	102	89	111	97	105	92	99	89	99	90	94	87	89	85	82	80		
90°	0	0	0		5.00	118	100	112	96	107	93	114	99	109	95	104	92	102	93	98	90	93	88	86	83		
100°	0	0	0		10.00	125	104	121	102	118	100	120	103	117	101	114	99	109	99	107	97	101	95	93	91		
110°	0	0	0																								
120°	0	0	0																								
130°	0	0	0																								
140°	0	0	0																								
150°	0	0	0																								
160°	0	0	0																								
170°	1	1	0																								
180°	1	1	1																								

