


東芝照明器具配光データシート

名 称		東芝LED器具		θ 	
形 名		LEKT425401L-LD9			ϕ 
効 率	F 	0 %			
	F 	100 %			
	F 	100 %			
	器具光束	3450 lm			
保 守 率	良	0.86			
	中	0.81			
	否	0.72			
最大取付間隔				備 考	
前 面		A-A	1.27 H		
反射面		B-B	1.23 H		

光度 (cd/1000lm)				反射率 (%)	天井 壁 床	80						70						50				30		20	0
$\theta \backslash \phi$	A-A	B-B	C-C			70		50		30		70		50		30		50		30		30		10	0
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
0°	329	329	329			固有照明率 (×0.01)																			
10°	323	322	322																						
20°	307	303	305																						
30°	282	273	277																						
40°	250	235	242																						
50°	215	189	200																						
60°	175	139	160																						
70°	127	84	112																						
80°	76	32	62																						
90°	0	0	0																						
100°	0	0	0																						
110°	0	0	0																						
120°	0	0	0																						
130°	0	0	0																						
140°	0	0	0																						
150°	0	0	0																						
160°	0	0	0																						
170°	1	1	0																						
180°	1	1	1																						

