


東芝照明器具配光データシート

名 称		東芝LED器具		θ	
形 名		LEKT425251N-LD9			
効 率	F 	0 %		ϕ	
	F 	100 %			
	F 	100 %			
	器具 光束	2400 lm			
保 守 率		良	0.86	備 考	
		中	0.81		
		否	0.72		
最大取付間隔					
		A-A	1.27 H		
前 面		カバー (乳白)			
反射面		塗装 (白)			
		B-B	1.23 H		

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50						30		20	0					
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70		50		30		70		50		30		50		30		30		10	0							
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0					
						固有照明率 (×0.01)																										
0°	329	329	329	室指数	0.60																											
10°	323	322	322		0.80																											
20°	307	303	305		1.00																											
30°	282	273	277		1.25																											
40°	250	235	242		1.50																											
50°	215	189	200		2.00																											
60°	175	139	160		2.50																											
70°	127	84	112		3.00																											
80°	76	32	62		4.00																											
90°	0	0	0		5.00																											
100°	0	0	0		10.00																											
110°	0	0	0																													
120°	0	0	0																													
130°	0	0	0																													
140°	0	0	0																													
150°	0	0	0																													
160°	0	0	0																													
170°	1	1	0																													
180°	1	1	1																													

