

東芝照明器具配光データシート

名 称		東芝LED器具		<div><div><div><div>θ</div><div></div></div><div><div>ϕ</div><div></div></div></div></div>				
形 名		LEKT425521HYN-LD9						
効 率	F	0 %		保守率	良	0.86		
	F	100 %			中	0.81		
	F	100 %			否	0.72		
	器具 光束	4850 lm		最大取付間隔				
前 面		カバー（乳白）		備考		A-A	1.27 H	
反射面		塗装（白）				B-B	1.23 H	

光度 (cd/1000lm)				反射率 (%)	天井	80						70						50						30		20	0			
$\theta \backslash \phi$	A-A	B-B	C-C			壁	70		50		30		70		50		30		50		30		30		10	0				
							30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	20	0
室指数				固有照明率 (×0.01)																										
0°				61	56	47	44	38	37	60	55	46	44	38	37	45	43	37	36	36	36	36	31	29						
10°				73	67	59	55	49	47	71	65	58	54	49	47	56	53	48	46	47	46	41	39							
20°				81	72	66	61	57	54	78	71	65	61	56	53	62	59	54	52	53	52	47	45							
30°				88	78	75	68	65	61	85	77	73	67	64	60	70	66	62	59	60	58	54	51							
40°				93	82	81	73	71	66	90	81	79	72	70	65	75	70	68	64	65	63	59	56							
50°				102	89	91	81	82	75	98	87	88	80	80	74	84	78	77	73	74	71	67	65							
60°				107	92	97	86	89	80	103	91	94	84	87	79	89	82	83	78	79	76	72	70							
70°				111	95	102	89	94	84	107	93	99	88	92	83	93	86	88	82	84	80	76	74							
80°				115	98	108	94	102	89	111	97	105	92	99	89	99	90	94	87	89	85	82	80							
90°				118	100	112	96	107	93	114	99	109	95	104	92	102	93	98	90	93	88	86	83							
100°				125	104	121	102	118	100	120	103	117	101	114	99	109	99	107	97	101	95	93	91							

