

東芝照明器具配光データシート

名 称		東芝LED器具		θ 
形 名		LEKT425321YW-LD9		
効 率	F 	0 %		
	F 	100 %		
	F 	100 %		
	器具光束	2850 lm		
最大取付間隔				
前 面		カバー (乳白)		
反射面		塗装 (白)		
		A-A	1.27 H	
		B-B	1.23 H	

光度 (cd/1000lm)				反射率 (%)	天井 壁 床	80						70						50				30		20	0		
$\theta \backslash \phi$	A-A	B-B	C-C			70		50		30		70		50		30		50		30		30		10	0		
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数					固有照明率 (×0.01)																						
0°		329	329	329	0.60	61	56	47	44	38	37	60	55	46	44	38	37	45	43	37	36	36	36	31	29		
10°		323	322	322	0.80	73	67	59	55	49	47	71	65	58	54	49	47	56	53	48	46	47	46	41	39		
20°		307	303	305	1.00	81	72	66	61	57	54	78	71	65	61	56	53	62	59	54	52	53	52	47	45		
30°		282	273	277	1.25	88	78	75	68	65	61	85	77	73	67	64	60	70	66	62	59	60	58	54	51		
40°		250	235	242	1.50	93	82	81	73	71	66	90	81	79	72	70	65	75	70	68	64	65	63	59	56		
50°		215	189	200	2.00	102	89	91	81	82	75	98	87	88	80	80	74	84	78	77	73	74	71	67	65		
60°		175	139	160	2.50	107	92	97	86	89	80	103	91	94	84	87	79	89	82	83	78	79	76	72	70		
70°		127	84	112	3.00	111	95	102	89	94	84	107	93	99	88	92	83	93	86	88	82	84	80	76	74		
80°		76	32	62	4.00	115	98	108	94	102	89	111	97	105	92	99	89	99	90	94	87	89	85	82	80		
90°		0	0	0	5.00	118	100	112	96	107	93	114	99	109	95	104	92	102	93	98	90	93	88	86	83		
100°		0	0	0	10.00	125	104	121	102	118	100	120	103	117	101	114	99	109	99	107	97	101	95	93	91		
110°		0	0	0																							
120°		0	0	0																							
130°		0	0	0																							
140°		0	0	0																							
150°		0	0	0																							
160°		0	0	0																							
170°		1	1	0																							
180°		1	1	1																							

