


東芝照明器具配光データシート

名 称		東芝LED器具		<div><div><div>θ</div><div></div></div><div><div>ϕ</div><div></div></div></div>				
形 名		LEKT812641L-LS2						
効 率	F 	6 %		保 守 率	良	0.88		
	F 	94 %			中	0.86		
	F 	100 %			否	0.81		
	器具 光束	5800 lm		最大取付間隔				
前 面	カバー（乳白）					備 考	A-A	1.27 H
反射面	塗装（白）						B-B	1.23 H

光度 (cd/1000lm)				反射率 (%)	天井	80						70						50				30		20	0							
$\theta \backslash \phi$	A-A	B-B	C-C			壁	70			50			30			70			50			30			50		30		30		10	0
							30	10		30	10		30	10		30	10		30	10		30	10		30	10		30	10		30	10
				室指数	固有照明率 (×0.01)																											
0°				0.60	60	55	46	43	37	36	58	54	44	42	36	35	43	41	35	34	34	33	29	27								
10°				0.80	72	65	57	54	48	46	69	63	56	53	47	45	53	51	45	44	44	43	38	36								
20°				1.00	79	71	64	60	55	52	76	69	63	59	54	51	59	56	52	50	50	49	44	41								
30°				1.25	86	77	73	67	63	59	83	75	71	65	61	58	67	63	59	56	57	55	50	47								
40°				1.50	91	81	78	71	69	64	88	78	76	70	67	63	72	67	64	61	61	59	55	52								
50°				2.00	100	87	88	79	79	72	96	85	85	77	77	71	80	74	73	69	70	67	62	60								
60°				2.50	105	90	94	83	86	77	100	88	91	82	83	76	85	79	79	74	75	72	67	64								
70°				3.00	108	93	99	87	91	81	104	91	95	85	88	80	89	82	83	78	79	75	71	68								
80°				4.00	113	96	105	91	99	87	108	94	101	89	95	85	94	86	89	83	84	80	76	73								
90°				5.00	116	98	109	94	103	90	111	96	105	92	100	89	97	89	93	86	87	83	80	77								
100°				10.00	122	102	118	100	115	98	117	100	114	98	110	96	105	95	102	93	95	90	87	84								
110°																																
120°																																
130°																																
140°																																
150°																																
160°																																
170°																																
180°																																

