


東芝照明器具配光データシート

名 称		東芝LED器具		θ 	
形 名		LEKT207161WW-LD9			ϕ 
効 率	F 	6 %			
	F 	94 %			
	F 	100 %			
	器具光束	1460 lm			
		保守率	良	0.83	
			中	0.81	
			否	0.77	
		最大取付間隔		備考	
前 面		カバー（乳白）			
反射面		塗装（白）			
		A-A	1.27 H		
		B-B	1.23 H		

光度 (cd/1000lm)				反射率 (%)	天井	80			70			50			30		20	0
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70	50	30	70	50	30	50	30	50	30	30	10	0
0°	301	301	301		床	30	10	30	10	30	10	30	10	30	10	30	10	0
10°	296	295	295		室指数 固有照明率 (×0.01)													
20°	282	278	280	0.60	60	55	46	43	37	36	58	54	44	42	36	35	42	41
30°	259	250	255	0.80	72	65	57	54	48	46	69	63	56	53	47	45	53	51
40°	229	215	222	1.00	79	71	64	60	55	52	76	69	63	59	54	51	59	56
50°	193	174	183	1.25	86	77	73	67	63	59	83	75	70	65	61	58	66	63
60°	155	128	142	1.50	91	80	78	71	69	64	88	78	76	70	67	63	71	67
70°	118	78	100	2.00	100	87	88	79	79	72	95	84	85	77	77	71	80	74
80°	83	30	62	2.50	104	90	94	83	86	77	100	88	91	81	83	76	85	78
90°	55	2	34	3.00	108	93	99	87	91	81	103	90	95	85	88	80	89	81
100°	33	1	18	4.00	113	96	105	91	99	87	108	94	101	89	95	85	94	86
110°	20	1	10	5.00	116	98	109	94	103	90	111	96	105	92	100	88	97	88
120°	12	1	7	10.00	122	102	118	100	115	97	117	100	113	98	110	96	104	94
130°	9	1	6															
140°	7	1	5															
150°	6	1	3															
160°	4	0	2															
170°	2	1	2															
180°	1	1	1															

