

東芝照明器具配光データシート

名 称		東芝LED器具		<div><div><div><div><div></div><div>θ</div></div><div><div></div><div>0°</div></div></div><div><div><div><div></div><div>φ</div></div><div><div></div><div>A</div><div>C</div><div>C</div><div>A</div></div><div><div></div><div>B</div><div>C</div><div>C</div><div>B</div></div></div></div></div></div>		
形 名		LEKT223161W-LD9				
効 率	F $\frac{1}{2}$	5 %		保 守 率	良	0.83
	F $\frac{3}{4}$	95 %			中	0.81
	F○	100 %			否	0.77
	器具 光束	1510 lm		最大取付間隔		
前 面		カバー（乳白）		備 考	A-A	1.27 H
反射面		塗装（白）			B-B	1.23 H

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50				30		20	0			
θ \ φ	A-A	B-B	C-C		壁	70		50		30		70		50		30		50		30		30		10	0			
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0			
0°	304	304	304		固有照明率 (×0.01)																							
10°	299	298	299	室指数																								
20°	286	281	283	0.60	60	55	46	43	37	36	58	54	45	43	36	35	43	41	35	34	34	34	29	27				
30°	263	253	258	0.80	72	65	57	54	48	46	69	63	56	53	47	45	53	51	46	44	44	43	38	36				
40°	233	218	226	1.00	79	71	65	60	55	52	76	69	63	59	54	51	60	57	52	50	50	49	44	42				
50°	198	176	187	1.25	87	77	73	67	63	59	83	75	71	65	62	58	67	63	59	57	57	55	50	48				
60°	159	129	145	1.50	92	81	79	71	69	64	88	79	76	70	67	63	72	67	65	61	62	60	55	52				
70°	121	79	103	2.00	100	87	88	79	79	72	96	85	86	77	77	71	80	75	74	69	70	68	63	60				
80°	86	30	65	2.50	105	90	94	83	86	77	100	88	91	82	84	76	85	79	79	74	75	72	68	65				
90°	58	2	38	3.00	108	93	99	87	91	81	104	91	96	85	89	80	89	82	84	78	79	76	72	69				
100°	40	1	20	4.00	113	96	105	91	99	87	108	94	102	90	96	85	95	86	90	83	85	81	77	74				
110°	13	1	1	5.00	116	98	109	94	104	90	111	96	105	92	100	89	98	89	94	86	88	84	80	77				
120°	0	1	1	10.00	122	102	119	100	115	98	117	100	114	98	111	96	105	95	103	93	96	90	88	85				
130°	0	1	0																									
140°	0	0	0																									
150°	0	0	0																									
160°	0	0	0																									
170°	1	0	0																									
180°	1	1	0																									

