



東芝照明器具配光データシート

名 称		東芝LED器具		θ 
形 名		LEKR740851WW-LD9		
効 率	F 	0 %		ϕ 
	F 	100 %		
	F 	100 %		
	器具光束	7300 lm		
最大取付間隔				備考
前 面		A-A	1.32 H	
反射面		塗装（白）	B-B	

光度 (cd/1000lm)				反射率 (%)	天井	80						70						50						30	20	0
$\theta \setminus \phi$	A-A	B-B	C-C		壁																					
0°	361	361	361		床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0
10°	357	354	356		固有照明率 (×0.01)																					
20°	344	333	339		室指数																					
30°	323	299	313		0.60	64	59	50	47	41	40	62	57	49	47	41	40	47	45	40	39	39	39	34	33	
40°	281	255	276		0.80	76	69	62	59	53	51	74	68	61	58	53	51	59	57	52	50	51	50	45	43	
50°	230	204	223		1.00	84	75	70	65	61	58	81	74	69	64	60	57	66	63	59	57	57	56	52	50	
60°	162	148	164		1.25	92	81	79	72	70	65	89	80	77	71	69	65	74	70	67	64	65	63	59	57	
70°	49	89	90		1.50	97	85	85	77	76	70	94	84	83	76	75	70	79	74	72	69	70	68	64	62	
80°	7	34	9		2.00	105	91	95	85	87	79	101	90	92	84	85	78	88	82	82	77	79	76	72	70	
90°	0	0	0		2.50	110	95	101	89	93	84	106	93	98	88	91	83	93	86	87	82	84	80	77	75	
100°	0	0	0		3.00	113	97	105	92	98	88	109	95	102	91	96	87	97	89	92	85	88	84	81	79	
110°	0	0	0		4.00	117	100	111	96	105	93	113	98	108	95	103	92	101	93	98	90	93	89	86	84	
120°	0	0	0		5.00	120	102	115	98	110	96	116	100	111	97	107	95	104	95	101	93	96	91	89	87	
130°	0	0	0		10.00	126	105	123	103	120	102	121	104	118	102	116	101	111	100	109	99	103	97	95	93	
140°	0	0	0																							
150°	0	0	0																							
160°	0	0	0																							
170°	1	1	1																							
180°	1	1	1																							

