


東芝照明器具配光データシート

名 称		東芝LED器具		<div><div>θ</div><div></div></div>			
形 名		LEKR760901L-LD9					
効 率	F 	0 %		保 守 率	良	0.8 1	
	F 	1 0 0 %			中	0.7 7	
	F 	1 0 0 %			否	0.6 8	
	器具 光束	7 8 0 0 lm		最大取付間隔			
前 面				備 考		A-A	1.3 2 H
反射面		塗装（白）				B-B	1.2 3 H

光度 (cd/1000lm)				反 射 率 (%)	天井 壁 床	80						70						50						30		20	0		
$\theta \backslash \phi$	A-A	B-B	C-C			70			50			30			70			50			30			50		30		10	0
						70	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0	
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0	
室指数				固 有 照 明 率 (×0.01)																									
0°	361	361	361	0.60	64	59	50	47	41	40	62	57	49	47	41	40	47	45	40	39	39	39	39	34	33				
10°	357	354	356	0.80	76	69	62	59	53	51	74	68	61	58	53	51	59	57	52	50	51	50	45	43					
20°	344	333	339	1.00	84	75	70	65	61	58	81	74	69	64	60	57	66	63	59	57	57	56	52	50					
30°	323	299	313	1.25	92	81	79	72	70	65	89	80	77	71	69	65	74	70	67	64	65	63	59	57					
40°	281	255	276	1.50	97	85	85	77	76	70	94	84	83	76	75	70	79	74	72	69	70	68	64	62					
50°	230	204	223	2.00	105	91	95	85	87	79	101	90	92	84	85	78	88	82	82	77	79	76	72	70					
60°	162	148	164	2.50	110	95	101	89	93	84	106	93	98	88	91	83	93	86	87	82	84	80	77	75					
70°	49	89	90	3.00	113	97	105	92	98	88	109	95	102	91	96	87	97	89	92	85	88	84	81	79					
80°	7	34	9	4.00	117	100	111	96	105	93	113	98	108	95	103	92	101	93	98	90	93	89	86	84					
90°	0	0	0	5.00	120	102	115	98	110	96	116	100	111	97	107	95	104	95	101	93	96	91	89	87					
100°	0	0	0	10.00	126	105	123	103	120	102	121	104	118	102	116	101	111	100	109	99	103	97	95	93					
110°	0	0	0																										
120°	0	0	0																										
130°	0	0	0																										
140°	0	0	0																										
150°	0	0	0																										
160°	0	0	0																										
170°	1	1	1																										
180°	1	1	1																										

