



東芝照明器具配光データシート

名 称		東芝LED器具		θ 		
形 名		LEKR741851L-LD9				
効 率	F 	0 %		ϕ 		
	F 	100 %				
	F 	100 %				
	器具光束	6600 lm				
		保守率	良		0.81	
			中		0.77	
			否		0.68	
		最大取付間隔			備考	
前 面	バツフル (白)		A-A			1.32 H
反射面	塗装 (白)		B-B			1.13 H

光度 (cd/1000lm)				反射率 (%)	天井 壁 床	80						70						50				30		20	0			
$\theta \backslash \phi$	A-A	B-B	C-C			70			50			30			70			50			30		50	30	10	0		
						70	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
室指数					固有照明率 (×0.01)																							
0°					65	60	51	49	43	41	63	59	50	48	42	41	49	47	42	41	41	40	36	34				
10°					78	71	64	60	55	53	76	69	63	59	55	53	61	58	54	52	53	51	47	45				
20°					85	76	72	66	63	59	82	75	70	66	62	59	68	64	60	58	59	58	53	51				
30°					93	82	80	73	71	67	90	81	78	73	70	66	75	71	68	65	66	64	60	58				
40°					98	86	86	78	77	72	94	84	84	77	76	71	80	75	74	70	71	69	65	63				
50°					106	92	96	85	88	80	102	90	93	84	86	79	89	82	83	78	80	77	73	71				
60°					110	95	101	90	94	85	106	94	99	88	92	84	94	86	88	83	85	81	78	76				
70°					114	97	106	93	99	88	110	96	103	92	97	88	97	89	92	86	89	85	82	80				
80°					118	100	112	97	106	93	114	99	108	95	103	92	102	93	98	91	93	89	86	84				
90°					120	102	115	99	110	96	116	100	111	98	107	95	105	95	102	93	96	92	89	87				
100°					126	105	123	104	120	102	121	104	119	102	116	101	111	100	109	99	103	97	95	93				
110°																												
120°																												
130°																												
140°																												
150°																												
160°																												
170°																												
180°																												

