



東芝照明器具配光データシート

名 称		東芝LED器具		<div><div>θ</div><div></div></div> <div><div>ϕ</div><div></div></div>			
形 名		LEKR761111L-LD9					
効 率	F 	0 %		保 守 率	良	0.8 1	
	F 	1 0 0 %			中	0.7 7	
	F 	1 0 0 %			否	0.6 8	
	器具 光束	8 9 0 0 lm					
前 面		バツフル (白)		最大取付間隔		備 考	
反射面		塗装 (白)		A-A	1.3 2 H		
				B-B	1.1 3 H		

光度 (cd/1000lm)				反射率 (%)	天井 壁 床	80						70						50				30		20	0				
$\theta \backslash \phi$	A-A	B-B	C-C			70		50		30		70		50		30		50		30		30		10	0				
						70	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0				
0°	393	393	393			固有照明率 (×0.01)																							
10°	389	380	384																										
20°	375	347	360																										
30°	349	301	324																										
40°	303	248	275																										
50°	249	188	214																										
60°	173	125	149																										
70°	51	63	76																										
80°	9	22	19																										
90°	0	1	1																										
100°	0	0	0																										
110°	0	0	0																										
120°	0	0	0																										
130°	0	0	0																										
140°	0	0	0																										
150°	0	0	0																										
160°	0	0	0																										
170°	1	1	1																										
180°	1	1	1																										

