



東芝照明器具配光データシート

名 称		東芝LED器具		<div><div>θ</div><div></div></div> <div><div>ϕ</div><div></div></div>		
形 名		LEKR761901W-LD9				
効 率	F 	0 %		保守 率	良	0.81
	F 	100 %			中	0.77
	F 	100 %			否	0.68
	器具 光束	7700 lm		最大取付間隔		
前 面		バツフル（白）		備 考	<div><div>A-A</div><div>1.32 H</div></div> <div><div>B-B</div><div>1.13 H</div></div>	
反射面		塗装（白）				

光度 (cd/1000lm)				反射率 (%)	天井	80						70						50						30		20	0					
$\theta \backslash \phi$	A-A	B-B	C-C			壁	70			50			30			70			50			30			50		30		10	0		
							30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	20	0
室指数				固有照明率 (×0.01)																												
0°				65	60	51	49	43	41	63	59	50	48	42	41	49	47	42	41	41	40	36	34									
10°				78	71	64	60	55	53	76	69	63	59	55	53	61	58	54	52	53	51	47	45									
20°				85	76	72	66	63	59	82	75	70	66	62	59	68	64	60	58	59	58	53	51									
30°				93	82	80	73	71	67	90	81	78	73	70	66	75	71	68	65	66	64	60	58									
40°				98	86	86	78	77	72	94	84	84	77	76	71	80	75	74	70	71	69	65	63									
50°				106	92	96	85	88	80	102	90	93	84	86	79	89	82	83	78	80	77	73	71									
60°				110	95	101	90	94	85	106	94	99	88	92	84	94	86	88	83	85	81	78	76									
70°				114	97	106	93	99	88	110	96	103	92	97	88	97	89	92	86	89	85	82	80									
80°				118	100	112	97	106	93	114	99	108	95	103	92	102	93	98	91	93	89	86	84									
90°				120	102	115	99	110	96	116	100	111	98	107	95	105	95	102	93	96	92	89	87									
100°				126	105	123	104	120	102	121	104	119	102	116	101	111	100	109	99	103	97	95	93									
110°																																
120°																																
130°																																
140°																																
150°																																
160°																																
170°																																
180°																																

