


東芝照明器具配光データシート

名 称		東芝LED器具		
形 名		LEKR761901L-LD9		
効 率	F 	0 %		
	F 	1 0 0 %		
	F 	1 0 0 %		
	器具 光束	7 3 5 0 lm		
保 守 率		良	0.8 1	
		中	0.7 7	
		否	0.6 8	
前 面		最大取付間隔		
		A-A	1.3 2 H	
		B-B	1.1 3 H	
反射面		塗装（白）		



光度 (cd/1000lm)				反 射 率 (%)	天井 壁 床	80						70						50						30		20	0				
$\theta \backslash \phi$	A-A	B-B	C-C			70		50		30		70		50		30		50		30		30		10	0						
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0						
0°	393	393	393			固有照明率 (×0.01)																									
10°	389	380	384	室指数																											
20°	375	347	360	0.60	65	60	51	49	43	41	63	59	50	48	42	41	49	47	42	41	41	40	36	34							
30°	349	301	324	0.80	78	71	64	60	55	53	76	69	63	59	55	53	61	58	54	52	53	51	47	45							
40°	303	248	275	1.00	85	76	72	66	63	59	82	75	70	66	62	59	68	64	60	58	59	58	53	51							
50°	249	188	214	1.25	93	82	80	73	71	67	90	81	78	73	70	66	75	71	68	65	66	64	60	58							
60°	173	125	149	1.50	98	86	86	78	77	72	94	84	84	77	76	71	80	75	74	70	71	69	65	63							
70°	51	63	76	2.00	106	92	96	85	88	80	102	90	93	84	86	79	89	82	83	78	80	77	73	71							
80°	9	22	19	2.50	110	95	101	90	94	85	106	94	99	88	92	84	94	86	88	83	85	81	78	76							
90°	0	1	1	3.00	114	97	106	93	99	88	110	96	103	92	97	88	97	89	92	86	89	85	82	80							
100°	0	0	0	4.00	118	100	112	97	106	93	114	99	108	95	103	92	102	93	98	91	93	89	86	84							
110°	0	0	0	5.00	120	102	115	99	110	96	116	100	111	98	107	95	105	95	102	93	96	92	89	87							
120°	0	0	0	10.00	126	105	123	104	120	102	121	104	119	102	116	101	111	100	109	99	103	97	95	93							
130°	0	0	0																												
140°	0	0	0																												
150°	0	0	0																												
160°	0	0	0																												
170°	1	1	1																												
180°	1	1	1																												

