


東芝照明器具配光データシート

名 称	東芝LED器具			θ 		
形 名	LEKT750451W-LD9					
効 率	F 	0 %		保 守 率	良	0.81
	F 	100 %			中	0.77
	F 	100 %			否	0.68
	器具光束	4400 lm		最大取付間隔		
前 面				備 考	A-A	1.23 H
反射面	塗装(白)				B-B	1.27 H

光度(cd/1000lm)				反射率 (%)	天井 壁 床	80						70						50				30		20	0			
$\theta \backslash \phi$	A-A	B-B	C-C			70		50		30		70		50		30		50		30		30		10	0			
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
						固有照明率(×0.01)																						
0°	330	330	330	室指数																								
10°	323	325	324	0.60	61	57	47	45	38	37	60	55	46	44	38	37	45	43	37	36	37	36	31	30				
20°	304	310	307	0.80	74	67	59	55	50	48	71	65	58	55	49	47	56	53	48	47	47	46	41	39				
30°	273	286	279	1.00	81	72	66	62	57	54	78	71	65	61	56	53	62	59	55	53	53	52	47	45				
40°	233	255	243	1.25	89	79	75	69	65	61	86	77	73	68	64	61	70	66	62	60	60	59	54	52				
50°	188	221	201	1.50	94	83	81	73	71	66	90	81	79	72	70	66	75	70	68	65	66	63	59	57				
60°	137	177	159	2.00	102	89	91	81	82	75	99	87	88	80	80	74	84	78	77	73	74	72	67	65				
70°	84	129	109	2.50	107	92	97	86	89	80	103	91	94	85	87	79	89	82	83	78	80	77	73	70				
80°	32	72	58	3.00	111	95	102	89	94	84	107	93	99	88	92	83	93	86	88	82	84	80	77	75				
90°	0	0	1	4.00	116	98	108	94	102	90	111	97	105	93	99	89	99	90	94	87	90	85	82	80				
100°	0	0	0	5.00	118	100	112	96	107	93	114	99	109	95	104	92	102	93	98	90	93	89	86	84				
110°	0	0	0	10.00	125	104	121	102	118	100	120	103	117	101	114	99	109	99	107	97	101	95	93	91				
120°	0	0	0																									
130°	0	0	0																									
140°	0	0	0																									
150°	0	0	0																									
160°	0	0	0																									
170°	0	0	0																									
180°	0	0	0																									

