



東芝照明器具配光データシート

名 称		東芝LED器具		θ 
形 名		LEKT770901L-LD9		
効 率	F 	0 %		ϕ 
	F 	100 %		
	F 	100 %		
	器具光束	8100 lm		
最大取付間隔				備考
前 面		A-A	1.23 H	
反射面		塗装（白）	B-B	

光度 (cd/1000lm)				反射率 (%)	天井	80			70			50			30		20	0
$\theta \setminus \phi$	A-A	B-B	C-C		壁	70	50	30	70	50	30	50	30	50	30	30	10	0
0°	330	330	330	室指数	床	30	10	30	10	30	10	30	10	30	10	30	10	0
10°	323	325	324		固有照明率 (×0.01)													
20°	304	310	307	0.60	61	57	47	45	38	37	60	55	46	44	38	37	45	43
30°	273	286	279	0.80	74	67	59	55	50	48	71	65	58	55	49	47	56	53
40°	233	255	243	1.00	81	72	66	62	57	54	78	71	65	61	56	53	62	59
50°	188	221	201	1.25	89	79	75	69	65	61	86	77	73	68	64	61	70	66
60°	137	177	159	1.50	94	83	81	73	71	66	90	81	79	72	70	66	75	70
70°	84	129	109	2.00	102	89	91	81	82	75	99	87	88	80	80	74	84	78
80°	32	72	58	2.50	107	92	97	86	89	80	103	91	94	85	87	79	89	82
90°	0	0	1	3.00	111	95	102	89	94	84	107	93	99	88	92	83	93	86
100°	0	0	0	4.00	116	98	108	94	102	90	111	97	105	93	99	89	99	90
110°	0	0	0	5.00	118	100	112	96	107	93	114	99	109	95	104	92	102	93
120°	0	0	0	10.00	125	104	121	102	118	100	120	103	117	101	114	99	109	99
130°	0	0	0															
140°	0	0	0															
150°	0	0	0															
160°	0	0	0															
170°	0	0	0															
180°	0	0	0															

