


東芝照明器具配光データシート

名 称		東芝LED器具		θ 
形 名		LEKT770651N-LD9		
効 率	F 	0 %		
	F 	100 %		
	F 	100 %		
	器具光束	6500 lm		
前 面		最大取付間隔		備考
		A-A	1.23 H	
反射面		塗装（白）	B-B	1.27 H

光度 (cd/1000lm)				反射率 (%)	天井	80						70						50						30		20	0			
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70			50			30			70			50			30			50		30		10	0	
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0
						固有照明率 (×0.01)																								
0°	330	330	330	室指数	0.60	61	57	47	45	38	37	60	55	46	44	38	37	45	43	37	36	37	36	31	30					
10°	323	325	324	0.80	74	67	59	55	50	48	71	65	58	55	49	47	56	53	48	47	47	46	41	39						
20°	304	310	307	1.00	81	72	66	62	57	54	78	71	65	61	56	53	62	59	55	53	53	52	47	45						
30°	273	286	279	1.25	89	79	75	69	65	61	86	77	73	68	64	61	70	66	62	60	60	59	54	52						
40°	233	255	243	1.50	94	83	81	73	71	66	90	81	79	72	70	66	75	70	68	65	66	63	59	57						
50°	188	221	201	2.00	102	89	91	81	82	75	99	87	88	80	80	74	84	78	77	73	74	72	67	65						
60°	137	177	159	2.50	107	92	97	86	89	80	103	91	94	85	87	79	89	82	83	78	80	77	73	70						
70°	84	129	109	3.00	111	95	102	89	94	84	107	93	99	88	92	83	93	86	88	82	84	80	77	75						
80°	32	72	58	4.00	116	98	108	94	102	90	111	97	105	93	99	89	99	90	94	87	90	85	82	80						
90°	0	0	1	5.00	118	100	112	96	107	93	114	99	109	95	104	92	102	93	98	90	93	89	86	84						
100°	0	0	0	10.00	125	104	121	102	118	100	120	103	117	101	114	99	109	99	107	97	101	95	93	91						
110°	0	0	0																											
120°	0	0	0																											
130°	0	0	0																											
140°	0	0	0																											
150°	0	0	0																											
160°	0	0	0																											
170°	0	0	0																											
180°	0	0	0																											

