



東芝照明器具配光データシート

名 称		東芝LED器具		<div><div>θ</div><div></div></div> <div><div>ϕ</div><div></div></div>		
形 名		LEKT751851N-LD9				
効 率	F 	0 %		保守率	良	0.81
	F 	100 %			中	0.77
	F 	100 %			否	0.68
	器具光束	8200 lm				
前 面		バツフル (白)		最大取付間隔		
反射面		塗装 (白)		A-A		1.27 H
				B-B		1.18 H
				備 考		

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50				30		20	0
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70		50		30		70		50		30		50		30		30		10	0
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
				室指数	固 有 照 明 率 (×0.01)																				
0°	347	347	347	0.60	62	57	48	45	39	38	60	56	47	45	39	38	46	44	38	37	37	37	32	31	
10°	342	335	340	0.80	74	68	60	56	51	49	72	66	59	56	50	48	57	54	49	48	48	47	42	40	
20°	327	310	319	1.00	82	73	68	63	58	55	79	72	66	62	57	55	63	60	56	54	54	53	48	46	
30°	302	274	287	1.25	89	79	76	70	66	62	86	78	74	69	65	62	71	67	63	61	62	60	55	53	
40°	269	230	247	1.50	94	83	82	74	72	67	91	82	80	73	71	67	76	71	69	66	67	65	60	58	
50°	233	180	202	2.00	103	89	92	82	83	76	99	88	89	81	81	75	85	79	78	74	75	73	68	66	
60°	185	128	153	2.50	108	93	98	86	90	81	104	91	95	85	88	80	90	83	84	79	81	77	74	71	
70°	133	75	98	3.00	111	95	103	90	95	85	107	94	99	89	93	84	94	86	89	83	85	81	78	75	
80°	72	27	43	4.00	116	99	109	94	103	90	112	97	105	93	100	89	99	91	95	88	90	86	83	81	
90°	0	3	4	5.00	119	100	113	97	107	94	114	99	109	96	104	93	102	93	99	91	94	89	86	84	
100°	0	0	0	10.00	125	104	121	102	118	101	120	103	117	101	114	100	109	99	107	97	101	96	94	91	
110°	0	0	0																						
120°	0	0	0																						
130°	0	0	0																						
140°	0	0	0																						
150°	0	0	0																						
160°	0	0	0																						
170°	0	0	0																						
180°	0	0	0																						

