



東芝照明器具配光データシート

名 称		東芝LED器具		θ 
形 名		LEKT751651L-LD9		
効 率	F 	0 %		ϕ 
	F 	100 %		
	F 	100 %		
	器具光束	5750 lm		
保 守 率	良	0.81		備 考
	中	0.77		
	否	0.68		
最大取付間隔				
A-A		1.27 H		
B-B		1.18 H		

光度 (cd/1000lm)				反射率 (%)	天井 壁 床	80						70						50				30		20	0		
$\theta \backslash \phi$	A-A	B-B	C-C			70		50		30		70		50		30		50		30		30		10	0		
						30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
室指数				固有照明率 (×0.01)																							
0°				62	57	48	45	39	38	60	56	47	45	39	38	46	44	38	37	37	37	37	32	31			
10°				74	68	60	56	51	49	72	66	59	56	50	48	57	54	49	48	48	47	42	40				
20°				82	73	68	63	58	55	79	72	66	62	57	55	63	60	56	54	54	53	48	46				
30°				89	79	76	70	66	62	86	78	74	69	65	62	71	67	63	61	62	60	55	53				
40°				94	83	82	74	72	67	91	82	80	73	71	67	76	71	69	66	67	65	60	58				
50°				103	89	92	82	83	76	99	88	89	81	81	75	85	79	78	74	75	73	68	66				
60°				108	93	98	86	90	81	104	91	95	85	88	80	90	83	84	79	81	77	74	71				
70°				111	95	103	90	95	85	107	94	99	89	93	84	94	86	89	83	85	81	78	75				
80°				116	99	109	94	103	90	112	97	105	93	100	89	99	91	95	88	90	86	83	81				
90°				119	100	113	97	107	94	114	99	109	96	104	93	102	93	99	91	94	89	86	84				
100°				125	104	121	102	118	101	120	103	117	101	114	100	109	99	107	97	101	96	94	91				
110°																											
120°																											
130°																											
140°																											
150°																											
160°																											
170°																											
180°																											

