


東芝照明器具配光データシート

名 称		東芝LED器具				θ 
形 名		LEKT423691HWW-LD9				
効 率	F 	5 %		保 守 率	良	0.88
	F 	95 %			中	0.86
	F 	100 %			否	0.81
	器具 光束	6500 lm		最大取付間隔		
前 面		カバー（乳白）		A-A	1.27 H	
反射面		塗装（白）		B-B	1.23 H	
				備 考		

光度 (cd/1000lm)				反 射 率 (%)	天井	80			70			50			30		20	0
$\theta \setminus \phi$	A-A	B-B	C-C		壁	70	50	30	70	50	30	50	30	50	30	30	10	0
0°	304	304	304		床	30	10	30	10	30	10	30	10	30	10	30	10	0
10°	299	298	299		室指数 固有照明率 (×0.01)													
20°	286	281	283		0.60	60	55	46	43	37	36	58	54	45	43	35	43	41
30°	263	253	258		0.80	72	65	57	54	48	46	69	63	56	53	47	45	53
40°	233	218	226		1.00	79	71	65	60	55	52	76	69	63	59	54	51	60
50°	198	176	187		1.25	87	77	73	67	63	59	83	75	71	65	62	58	67
60°	159	129	145		1.50	92	81	79	71	69	64	88	79	76	70	67	63	72
70°	121	79	103		2.00	100	87	88	79	79	72	96	85	86	77	77	71	80
80°	86	30	65		2.50	105	90	94	83	86	77	100	88	91	82	84	76	85
90°	58	2	38		3.00	108	93	99	87	91	81	104	91	96	85	89	80	89
100°	40	1	20		4.00	113	96	105	91	99	87	108	94	102	90	96	85	95
110°	13	1	1		5.00	116	98	109	94	104	90	111	96	105	92	100	89	98
120°	0	1	1		10.00	122	102	119	100	115	98	117	100	114	98	111	96	105
130°	0	1	0															
140°	0	0	0															
150°	0	0	0															
160°	0	0	0															
170°	1	0	0															
180°	1	1	0															

