



東芝照明器具配光データシート

名 称		東芝LED器具		<div><div><div>θ</div><div></div></div><div><div>ϕ</div><div></div></div></div>		
形 名		LEKT425691HWW-LD9				
効 率	F 	0 %		保 守 率	良	0.86
	F 	100 %			中	0.81
	F 	100 %			否	0.72
	器具 光束	6150 lm		最大取付間隔		
前 面		カバー（乳白）		A-A		1.27 H
反射面		塗装（白）		B-B		1.23 H
				備考		

光度 (cd/1000lm)				反 射 率 (%)	天井	80			70			50			30		20	0
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70	50	30	70	50	30	50	30	50	30	30	10	0
0°	329	329	329		床	30	10	30	10	30	10	30	10	30	10	30	10	0
10°	323	322	322		室指数													
20°	307	303	305		固有照明率 (×0.01)													
30°	282	273	277		0.60	61	56	47	44	38	37	60	55	46	44	38	37	45
40°	250	235	242		0.80	73	67	59	55	49	47	71	65	58	54	49	47	56
50°	215	189	200		1.00	81	72	66	61	57	54	78	71	65	61	56	53	62
60°	175	139	160		1.25	88	78	75	68	65	61	85	77	73	67	64	60	70
70°	127	84	112		1.50	93	82	81	73	71	66	90	81	79	72	70	65	75
80°	76	32	62		2.00	102	89	91	81	82	75	98	87	88	80	80	74	84
90°	0	0	0		2.50	107	92	97	86	89	80	103	91	94	84	87	79	89
100°	0	0	0		3.00	111	95	102	89	94	84	107	93	99	88	92	83	93
110°	0	0	0		4.00	115	98	108	94	102	89	111	97	105	92	99	89	99
120°	0	0	0		5.00	118	100	112	96	107	93	114	99	109	95	104	92	102
130°	0	0	0		10.00	125	104	121	102	118	100	120	103	117	101	114	99	109
140°	0	0	0															
150°	0	0	0															
160°	0	0	0															
170°	1	1	0															
180°	1	1	1															

