

東芝照明器具配光データシート

名称	LED照明器具
形名	LEDP88161

保守率	良	0.67
	中	0.63
	否	0.56

--	--

光源	名称	LEDランプ
	形名	LDA5L-G-E17 /S/40W
	光束	440 lm × 1

効率	F	14%
	F	75%
	F	89%
	器具光束	395 lm

最大取付間隔	
A-A	1.48 H
B-B	1.48 H

備考	
----	--

前面	
反射面	

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	155		
10°	153		
20°	153		
30°	152		
40°	148		
50°	142		
60°	126		
70°	102		
80°	87		
90°	71		
100°	33		
110°	23		
120°	18		
130°	13		
140°	10		
150°	8		
160°	6		
170°	3		
180°	0		

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	10	0		
室指数	照明率 (×0.01)																								
0.60	48	44	34	33	26	25	45	42	33	31	25	25	30	29	24	23	22	22	17	15					
0.80	58	52	44	41	35	33	55	50	42	40	34	32	39	37	31	30	29	29	24	21					
1.00	64	57	50	46	41	39	60	55	48	45	39	38	44	42	37	35	34	33	28	25					
1.25	71	63	57	53	48	45	67	60	55	51	46	43	50	47	43	41	40	39	33	30					
1.50	75	66	62	57	53	49	71	64	60	55	51	48	54	51	47	45	44	42	37	34					
2.00	83	72	71	64	62	57	78	69	68	62	60	55	62	57	55	52	51	49	44	40					
2.50	87	75	77	68	68	62	82	72	73	66	65	60	66	61	60	56	55	53	48	44					
3.00	91	78	81	71	73	65	86	75	77	69	70	63	70	64	64	60	59	56	51	47					
4.00	95	81	87	76	80	71	90	78	83	73	77	69	75	68	70	65	64	61	56	52					
5.00	98	83	91	78	85	74	93	80	87	76	81	72	78	71	74	68	67	64	59	55					
10.00	105	88	101	85	96	82	99	85	95	82	92	80	86	77	83	75	75	71	67	63					

