

東芝照明器具配光データシート

名 称		LED照明器具		保守率	良	0.67			
形 名		LEDP88062R			中	0.63			
					否	0.56			
光源	名称	LEDランプ		効率	F 	5%	最大取付間隔		
	形名	LDA6L-H-E17 /S			F 	80%			
	光束	440 lm × 1			F 	85%			
前面				器具 光束			A-A	1.27H	
反射面							B-B	1.27H	
								備考	

光度 (cd/1000lm)				反 射 率 (%)	天井		80						70						50						30		20	0				
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70			50			30			70			50			30			50		30		30		10	0	
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0
					室指数	照 明 率 (×0.01)																										
0°	289			0.60	53	49	41	39	34	33	51	48	40	38	33	33	39	37	33	32	32	31	27	26								
10°	283			0.80	64	58	52	49	44	42	61	56	51	48	43	42	48	46	42	41	41	40	36	34								
20°	268			1.00	70	63	58	54	50	48	67	61	57	53	50	47	54	51	48	46	46	45	41	39								
30°	244			1.25	76	68	65	60	58	54	74	66	64	59	56	53	60	57	54	52	52	51	47	45								
40°	214			1.50	81	71	70	64	63	58	78	69	68	63	61	58	65	61	59	56	56	55	51	49								
50°	179			2.00	88	76	79	70	72	65	84	74	76	69	70	65	72	67	67	63	63	61	58	55								
60°	126			2.50	91	79	84	74	77	70	88	77	81	73	75	69	76	70	71	67	67	65	61	59								
70°	53			3.00	94	81	87	77	82	73	91	79	84	75	79	72	79	73	75	70	71	68	64	62								
80°	24			4.00	98	83	92	80	87	77	94	82	89	79	85	76	83	76	79	73	75	71	68	66								
90°	13			5.00	100	85	96	82	91	79	96	83	92	81	88	78	85	78	82	76	77	73	71	68								
100°	12			10.00	105	88	102	86	100	85	101	86	98	85	96	83	91	82	89	81	83	78	76	74								
110°	12																															
120°	12																															
130°	7																															
140°	0																															
150°	0																															
160°	0																															
170°	0																															
180°	0																															

